



3350PMSMV

HID iCLASS SE 2k bit, Clamshell, Prgm SIO (iCLASS SE Clamshell Contactless Smart Card, 2k bit with 2 application areas, SIO Programmed Does Not Support Standard iCLASS), Plain



3350PMSMV

HID iCLASS SE 2k bit, Clamshell, Prgm SIO (iCLASS SE Clamshell Contactless Smart Card, 2k bit with 2 application areas, SIO Programmed Does Not Support Standard iCLASS), Plain

Technical specifications

System

Reading distance	5 to 10 cm
Card slot punch	Yes

Technology

Credential type	Smart card
Credential driftsfrekvens	13.56 MHz
Support technology	SIO 13,56 MHz

Printing

Direct surface printing	Yes
Thermal transfer printing	Yes

Ordering information

Minimum order quantity	100
Special card order form required	No

Physical

Surface cover	Plain
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	6.8 g
Colour	White

Environmental

Operating temperature	-40 to 70°C
Relative humidity	5 to 95% noncondensing



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 21 May 2024 - 14:03