



KIDDE
GLOBAL SOLUTIONS

3700CPGGMN

HID DESFire EV1, 8 kB memory, ISO, default NXP keys, PVC(MIFARE DESFire EV1 contactless Smart Card, SIO Programmed, PVC, plain white gloss back and front, sequential



3700CPGGMN

HID DESFire EV1, 8 kB memory, ISO, default NXP keys, PVC(MIFARE DESFire EV1 contactless Smart Card, SIO Programmed, PVC, plain white gloss back and front, sequential

Technical specifications

System

Reading distance	5 to 10 cm
Memory size	8 kB
No. of Mifare bytes CSN	7 Bytes (S70)
Card slot punch	No

Technology

Credential type	Smart card
Credential driftsfrekvens	13.56 MHz
Support technology	MIFARE DESFire EV1 (CSN) 13,56 MHz

Printing

Direct surface printing	Yes
Thermal transfer printing	Not recommended

Ordering information

Minimum order quantity	100
Special card order form required	Yes

Physical

Surface cover	Glossy
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	5 g
Shipping weight	13 g
Colour	White

Environmental

Operating temperature	-40 to 50°C
Storage temperature	-40 to 50°C
Relative humidity	5 to 95% noncondensing

Regulatory

Compliance	RoHS
------------	------