

# ATS1500A-MBC

## Advisor Advanced panel motherboard card



#### **Details**

• Replacement board for ATS1500A non IP panels ATS7700 not included

# ATS1500A-MBC

### **Advisor Advanced panel motherboard card**

#### **Technical specifications**

System				
Product line	Advisor Advanced			
Product type	Integrated Access Control			
Panel type	Hybrid			
Kit	No			
No. of keypads / readers	s 8			
Data Gathering Panels (DGP)	7			
No. of alarm groups	16			
Specified cable	WCAT52 / WCAT54 or equivalent			
Inputs				
Max. no. of inputs	32			
Onboard inputs	8			
Inputs plug-in expansion	1 8			
Outputs				
No. of outputs	128			
No. of onboard outputs	5			
Area				
No. of areas	4			
User / cards				
Max. no. of users	more than 2000			
Users with name	1000			
Max. no. of cards	2000 to 65532			
Max. no. of PIN codes	2000 to 65532			
Access control				
Standard doors on control panel	4			
Door groups	128			
Floor groups	128			
Intelligent doors on 4-door DGPs	28			
Communication				
Onboard transmission type	PSTN			
Transmission extension	GSM, GSM/GPRS, GSM/GPRS/IP			
Databus type	RS485			
Event log				
Alarm event log	14500			
Access event log	10000			
Electrical				
Mainboard current consumption	150 mA			
Max. system current	1000 mA			
Max. aux power current	750 mA (depends on backup power needs)			
Auto rosot fusos	5			

_	-						
Р	h	1/	C	ī	0	2	ı
		v	J		v	а	ı

•			
Physical dimensions	202 x 90 x 40 mm		
Housing	No housing		
Environmental			
Operating temperature	-10 to +55°C		
Relative humidity	95% noncondensing		
Regulatory			
EN50131 Grade	Grade 2		
Compliancy	CE		



Auto-reset fuses

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.