

DM796 Keygaurd With Micro Switch

General

The DM796 is a high quality, RED plastic keybox with supervision. When the breakable element is broken to remove the key or access card inside the unit, the micro switch is activated. The micro switch has a normally open and normally closed contact.



Details

- · Easy to install
- Surface mounting
- High quality micro switch
- Normally open and normally closed contacts
- Replaceable breaking element
- Key or access card can be fitted inside

DM796 Keygaurd With Micro Switch

Technical specifications

| Electrical | | | | | |
|-------------------------------------|--------|-------------------------------|-------------|--|--|
| Max. contact rate resistive load | | 6 A @ 24 VDC | | | |
| | | | | | |
| Physical | | | | | |
| Physical dimensions | | 142 x 125 x 45 mm (W x H x D) | | | |
| Colour | | Red (RAL 3020) | | | |
| Mounting type | | Surface mount | | | |
| Environme | ntal | | | | |
| Operating temperature | | -40 to +85°C | | | |
| Relative humidity | | max. 90% noncondensing | | | |
| Environment | | Indoor | | | |
| Compatible | produc | ts | | | |
| Category | Refere | nce I | Description | | |
| Detection | DM797 | | | | |
| device | | | | | |



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.