

# DMN960Y

## 990 Series Resettable Manual Call Point, Yellow, Complete With Back Box

### General

---

The DMN960Y is a surface mount, YELLOW addressable 990 Series manual call point with a high strength plastic housing. The LED indicator provides visual confirmation of alarm initiation. The test key (included with each unit) facilitates functional testing of the call point. The manual call point is delivered complete with resettable element.

### Operating Principles

---

The address of each call point is set at the commissioning stage by means of a seven-segment DIL switch. The device features plug and play terminal connections. A single alarm LED is provided on the call point and is controlled, independently of the call point, by the fire panel.

### Accessories

---

It is possible to surface or flush mount any of the call points in the range. Optional accessories to accommodate this are available separately.

### Approvals

---

All relevant manual call points in the range have been tested by LPC and approved by LPCB and a number of other approval authorities.



### Details

---

- Addressable manual call point
- LED alarm indicator
- Tamper resistant break glass design
- Easy to test with self reset
- Fast response
- Plug and play terminal connections for fast wiring
- Allow wiring continuity testing before fitting
- Resettable element fitted

# DMN960Y

## 990 Series Resettable Manual Call Point, Yellow, Complete With Back Box

### Technical specifications

---

#### General

Status indication	Red alarm LED
-------------------	---------------

---

#### Electrical

Communication voltage	5 to 9 V
-----------------------	----------

---

Current consumption	4 mA (LED on)
	750 $\mu$ A (Switch on surge, 4s)
	350 $\mu$ A (Quiescent/Alarm)

---

#### Physical

Physical dimensions	87 x 87 x 52 mm
---------------------	-----------------

---

Net weight	180 g
------------	-------

---

Colour	Yellow
--------	--------

---

Mounting type	Surface mount
---------------	---------------

---

Material (body)	Polycarbonate / ABS
-----------------	---------------------

---

#### Environmental

Operating temperature	-20 to +60°C (no icing)
-----------------------	-------------------------

---

Storage temperature	-30 to +80°C
---------------------	--------------

---

Relative humidity	0 to 95% noncondensing
-------------------	------------------------

---

Environment	Indoor
-------------	--------

---

IP rating	IP53
-----------	------

---