



DP652L

Apollo Series 65 optical smoke detector with blinking LED (55000-316)

General

The 650 Series smoke and heat detectors are designed for the highest effectiveness by utilising the latest technology.

Optical smoke detectors

These detectors use a pulsing LED and photo diode in a dark optical chamber. In the event of smoke from a fire entering the chamber, the light from the LED is scattered and registered by the photo diode.

Standard Base

The base is designed to enable detectors to be plugged in without any need for force - particularly useful when fitting to suspended ceilings. To make it even easier, the base has a "one way only" fit. All bases are lockable and contains no electronic parts that could be damaged during installation.

The detectors are polarity insensitive and bases are easy to wire with an earth connector.



Details

- Polarity insensitive
- Common base
- Elegant slim-line design
- Wide operating voltage

DP652L

Apollo Series 65 optical smoke detector with blinking LED (55000-316)

Technical specifications

General

Status indication	Clear LED, red in alarm
Compatibility	Conventional fire systems
Connectivity	2-wire zone

Electrical

Power supply type	Zone powered
Operating voltage	9 to 33 VDC
Current consumption	40 µA at 24 V (typical) (quiescent)

Detection

Detection principle	Optical light scatter
Zone length	< 2 km
Air velocity	Unaffected

Output

Output quantity	1
Output type and rating	Remote indicator
Remote alarm output	17 mA

Physical

Physical dimensions	50 x 100 mm (Detector + base) (H x W) 42 x 100 mm (Detector) (H x W)
Colour	White
Mounting type	Base mount

Environmental

Vandal proof	No
Operating temperature	-20 to +60°C (no icing)
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP43

Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
Certification	CPR
Standards	EN54:7