



FE130MD

Eco Line double magnetic lock, 300 Kgf, monitored, surface mount

Description

Eco Line double magnetic lock 2 x 300 kgf. Surface mounted, monitored.

Application

Medium Security applications for internal or external double leaf doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Details

- 2 x 300 Kgf holding power
- Monitored changeover
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Mounts easily with a minimum of tools

FE130MD

Eco Line double magnetic lock, 300 Kgf, monitored, surface mount

Technical specifications

General

| | |
|--------------|---------------|
| Product type | Magnetic lock |
|--------------|---------------|

Holding force

| | |
|---------------------------------------|-------------|
| Holding force kgf (Kilogram force) | 300 kgf x 2 |
|---------------------------------------|-------------|

| | |
|--------------------------|----------|
| Holding force N (Newton) | 3000 x 2 |
|--------------------------|----------|

Monitoring & status

| | |
|-----------|-----|
| Monitored | Yes |
|-----------|-----|

| | |
|---------------|-----|
| LED indicator | Yes |
|---------------|-----|

| | |
|--------------------|----|
| Door status switch | No |
|--------------------|----|

| | |
|----------------------|-----|
| Monitored changeover | Yes |
|----------------------|-----|

| | |
|----------------------|-----|
| Magnetic bond sensor | Yes |
|----------------------|-----|

Electrical

| | |
|--------------------|-------------|
| Power supply value | 12 / 24 VDC |
|--------------------|-------------|

| | |
|---------------------|--------------------------------|
| Current consumption | 440 mA (+/- 2,5% @ 13,5 V) x 2 |
|---------------------|--------------------------------|

Physical

| | |
|---------------------|------------------------------|
| Physical dimensions | 500 x 47 x 26 mm (W x H x D) |
|---------------------|------------------------------|

| | |
|--------|-----------|
| Colour | Aluminium |
|--------|-----------|
