



# TP-CP-KF-LG-25PK

25 pack, TruPortal credential, slender, TruPortal logo, Prximity (EM)

## Product overview

---

These TruPortal keyfobs are to be used on T100A, T100B and any other Carrier Fire & Security Transition reader supporting the CASI RUSCO Proximity protocol (CSN). The cards are unprogrammed and only the unique ID-number of the proximity chip, the so called Chip or Card Identification Number (CSN) is used by the readers.



## Details

---

- Read only for CSN

# TP-CP-KF-LG-25PK

25 pack, TruPortal credential, slender, TruPortal logo, Prximity (EM)

## Technical specifications

### System

Reading distance 5 to 10 cm

Custom data model No

Card slot punch No

### Technology

Credential type Proximity

Credential driftsfrekvens 125 KHz

Support technology 125 GE ProxLite/CASI Prox KHz

### Printing

Direct surface printing No

Thermal transfer printing No

### Ordering information

Minimum order quantity 1

Cards / tags in package 25

Special card order form No required

### Physical

Surface cover Glossy

Material PVC

Form factor Key Fob

Physical dimensions 105 x 115 x 32 mm

Net weight 270 g

Shipping weight 277 g

Colour Orange

### Environmental

Operating temperature -10 to 45°C

Storage temperature -10 to 45°C

Relative humidity 5 to 95% noncondensing

### Regulatory

Compliance RoHS

### Dimensions

110 mm x 20 mm x 3 mm

### Material

PVC

### Frequency

125 KHz

### Reading distance

0-10 cm

### For use on

T100A & T100B

### Color

Orange



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit [uk.firesecurityproducts.com](http://uk.firesecurityproducts.com) online or contact your sales representative.

Last updated on 29 March 2024 - 13:09