


TX-9001-03-1

Smart repeater for wireless 868Gen2 sensor range

If you encounter range problems for 868Gen2 Transmitters in a building, you can extend the range with this repeater. It is called smart repeater, because it can be used in different topologies and it repeats only known sensors and just all wireless traffic it receives. Sensor - Repeater - Panel configurations are possible as well as Sensor - Repeater - Repeater - Panel. The smart Repeater can build a network up to 15 Repeaters which allows for a large coverage for your Wireless installation.



Details

- Dual Antenna operation for improved sensor data reception
- Tamper protection
- Supervised by the panel
- Repeats only learned sensors to limit wireless traffic
- Diagnostics interface
- Power adaptor included

TX-9001-03-1

Smart repeater for wireless 868Gen2 sensor range

Technical specifications

General

Expander type	Wireless expander
Product line	Advisor Advanced, ATS Master, CS
Compatibility	868MHz Gen2 sensors

Electrical

Operating voltage	12 VDC +/-5%
Current consumption	52 mA +/-10%
Integrated power supply	No

Physical

Physical dimensions	165 x 117 x 42 mm
Net weight	285 gr

Environmental

Operating temperature	0 to +40°C
Relative humidity	80% non condensing



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit uk.firesecurityproducts.com online or contact your sales representative.

Last updated on 5 May 2023 - 9:32