

1336-LGGMN

DuoProx Card Prox with Mag Stripe Graphics Quality Both Sides - standard card includes, 26 bit format, plain white glossy finish for direct card printing on front and back, with printed



1336-LGGMN

DuoProx Card Prox with Mag Stripe Graphics Quality Both Sides - standard card includes, 26 bit format, plain white glossy finish for direct card printing on front and back, with printed

Technical specifications

System

Card slot punch	No
-----------------	----

Technology

Credential type	Magstripe, Proximity
Credential operating frequency	125 KHz
Support technology 125 KHz	EntryProx™, MaxiProx®, MiniProx®, pcProx™, Prox80™, ProxPoint® Plus, ProxPro®, ProxPro® II, ThinLine® II

Printing

Direct surface printing	Yes
-------------------------	-----

Ordering information

Minimum order quantity	100
Special card order form required	No

Physical

Surface cover	Plain
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	6.8 g
Colour	White

Environmental

Operating temperature	-45 to 70°C
-----------------------	-------------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.