

ACL805SUW-RDPX-B

ACL800 Keypad with EM/CASI/HID Prox reader, Wiegand, Surface mount, Black

Product description

These surface mount proximity ACL805SUW-RDPX-G readers includes a buzzer and a tri-color LED for state indication (access granted, access denied or idle). The ACL805SUW-RDPX-G is capable of reading Casi Rusco, EM and HID compatible cards/fobs (125 kHz) which is unique on the market. With the integrated keypad you can use Two-factor authentication with Card only, PIN Code only, Card or/and PIN Code.

The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.

Card technology

The readers are compatible with the TruPortal (125 KHz) credential range. The Proximity card type can be selected through DIP switches in "HID only" "HID and EM" "HID and Casi" "Casi only" or "EM only" and Wiegand outputs automatically according to the card type."

Compatibility

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.



Details

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Compatible with the TruPortal learn-in reader (TP-RDR-LRN)
- Backlight illumination
- Two-factor authentication
- Keypad with EM/CASI/HID Prox reader

ACL805SUW-RDPX-B

ACL800 Keypad with EM/CASI/HID Prox reader, Wiegand, Surface mount, Black

Technical specifications

System

Max. reader distance to panel 50 m

CSN (Card Serial Number) Yes

No. of LEDs 3

Language installation manual English

Technology

Reader type PIN keypad, Proximity

Reader operating-transmitting frequency 125 KHz

Supported technology EM4102, GE ProxLite/CASI Prox, HID Prox 125 kHz

Interface & connections

Interface Wiegand

Connector type Pigtail

Pigtail length 100 cm

Tamper type

Pry-off tamper No

Opening tamper Yes

Operation

Stand-alone No

PIN keypad Yes

PIN length 1 to 8 digits

Green LED Potential Free

Red LED Potential Free

Orange LED Idle mode

Illumination Blue backlight (programmable on/off control)

Buzzer 1 (internal)

Authentication Card, PIN Code, Card or/and PIN Code

Electrical

Power supply type VDC

Power supply value 9 to 14 VDC

Current consumption 150 mA at 12 VDC max.

Physical

Physical dimensions 100 x 94 x 30 mm

Net weight 300 g

Shipping weight 310 g

Colour Black

Material ABS

Form factor Oversized

Mounting type Surface mount

Environmental

Environment Indoor, Outdoor

Storage temperature -20 to +50°C

Regulatory

Compliance CE, RoHS



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 September 2023 - 9:53