



# AS586XXL

Outdoor siren - The Level - blue base, no cover, no battery



## Details

- Spirit level on top of the back plate to correctly align the AS580
- Low profile polycarbonate box with integrated strobe lens
- Double piezo sounder with 112 dB @ 1m sound output
- Highly weather resistant, IP55
- Easy wiring
- Easy diagnostics using the LEDs
- Tamper switch to protect from removal of cover or removal from surface

# AS586XXL

Outdoor siren - The Level - blue base, no cover, no battery

## Technical specifications

### General

Accessory group	Siren
Type	Outdoor siren
Sounder output (dB @ distance)	112 dB at 1 m (typical)

### Electrical

Operating voltage	10 to 14.5 V
Current consumption	420 mA (Sounder + Flash) 350 mA (Sounder) 110 mA (Flash light) 74 mA (Standby, LEDs ON cont) 57 mA (Standby, LEDs ON alt) 38 mA (Standby, LEDs OFF)

### Physical

Physical dimensions	371 x 225 x 56 mm
Material	Polycarbonate

### Environmental

Operating temperature	-25 to 55°C
IP rating	IP54

### Regulatory

Compliance	CE
------------	----

### Protection

PCB protection	Fully potted
Tamper & pry-off	Yes

### Sounder

Type	Double piezo
Sounder cut-off timer	5' or 15'
Frequency	1.8 to 3 kHz