

BS121N

Battery, 12 V, 1.2 Ah, Interlogix

Product overview

Sealed lead acid battery 12 V, 1.2 Ah with Fast-on 4.8 mm terminal type.



Details

- Maintenance free 12 VDC
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS121N

Battery, 12 V, 1.2 Ah, Interlogix

Technical specifications

General

Product type	Battery pack, NiCd battery, Sealed lead acid battery
--------------	--

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	1.2 Ah
Internal approx. resistance	75 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	0.36 A
Max. discharge current	6 A

Physical

Physical dimensions	97 x 43 x 53 mm
Net weight	0.596 kg
Shipping weight	0.596 kg
Material	Metal
Terminal type	Fast-on 4.8 mm

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliance	CE, RoHS 2, WEEE
Certification	VdS



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.