DC138

Industrial flush mount contact for steel door, high security grade 3, white

Requirements for grade 3 magnetic contacts

The grade 3 magnetic contacts are high security contacts which do meet the following requiments: preciseness of opening distance, magnet polarisation, strength of the magnet

Model with built in EOL resistors available

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



Details

- EN 50131-2-6 Grade 3 and VDS certified
- 2m cable
- Tamper protected
- Several European certifications

DC138

Industrial flush mount contact for steel door, high security grade 3, white

Technical specifications

General

Application type	Recessed mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination

Wired / wireless

Wired-wireless	Wired
Operating gap	12 mm

Electrical

Operating voltage	>250 V (breakdown voltage) max. 40 V (permissible operating voltage)
Voltage	max. 100 VDC
Contact power	max. 6 W or 6 VA
Switching current	max. 500mA
Contact resistance	max. 0.15 Ohm

Physical

Physical dimensions	Ø 3.2 mm x 2 m (cable dimensions)
Dimensions magnet	6 x 19 mm neodymium, axially polarized, in Ø 8 x 20 mm plastic sleeve with installation flange EF 8/20
Dimensions contact / sensor	8 x 32 mm with installation flange EF 8/20
Colour	White
Material	ABS

Environmental

Operating temperature	-25 to 70°C
IP rating	IP67

Regulatory

EN50131 grade	Grade 3
Certification	VdS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 18 June 2026 - 14:25