

# DMN700Y09-KITR

## MCP Yellow, Free Contact, Surface Mount, Resettable, Protection Cover - Spanish

### General

---

DMN700Y09-KITR is a yellow manual call point for surface mount applications. It offers a single pole, changeover contact with common, normally open and normally closed connections. It is supplied with a resettable break glass and test key.

### Installation

---

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

### Options

---

Through new standards and legislation, both break glass and re-settable operating elements may now be used. To provide the greatest 'flex-ability', the new MCP range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.



### Details

---

- Enhanced aesthetics
- Easy to install (plug and play)
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch

# DMN700Y09-KITR

## MCP Yellow, Free Contact, Surface Mount, Resettable, Protection Cover - Spanish

### Technical specifications

---

#### Isolation

Series resistance	NA
-------------------	----

---

#### Physical

Physical dimensions	92 x 115 x 59 mm (W x H x D)
Net weight	110 g
Colour	Yellow
Mounting type	Surface mount
Material (body)	PC / ABS

---

#### Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP24D

---

#### Cable Termination

0.5 to 2.5 mm<sup>2</sup>

---

#### Max. contact rating (resistive load)

2A @ 30 VDC

---

#### Compatible products

Category	Reference	Description
Detection device	DMN782	Hinged transparent MCP protection cover
Detection device	DMN784	Replacement test key for Manual Call Points, 10 pack
Detection device	DMN787Y	Surface Mounting Box With Earth Connector, Yellow
Detection device	DMN789	Replacement Pluggable Connectors For Manual Call Points (10 Pack)
Detection device	DMN800	Resettable element for Manual Call Point

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [firesecurityproducts.com](https://firesecurityproducts.com) online or contact your sales representative.

Last updated on 3 July 2023 - 9:40