


LNL-1320-S3

Dual reader interface module

Overview

Lenel offers a Dual Reader Interface (DRI) module for access control solutions. Most access control card readers, keypads, or readers with keypads that use standard Wiegand Data1/Data0 or Clock/Data communication are supported, as are those that support the bidirectional RS-485 Open Supervised Device Protocol (OSDP™). Lock, unlock, and facility code offline access modes are supported on all readers connected to the DRI. Each DRI supports up to 16 different card formats as well as issue codes for both magnetic and Wiegand card formats.

The DRI provides a vital link between the Intelligent System Controller (ISC) and the card reader attached to the interface. As many as 32 DRI modules can be multidropped using RS-485 2-wire or 4-wire communication up to 4,000 feet per port away from the ISC. Each DRI module is individually addressed for increased reporting capabilities with OnGuard® access control software applications. The DRI includes eight inputs that support normally open, normally closed, supervised, and non-supervised circuits. In addition, six output relays support fail-safe or fail-secure operation.



Details

- Supports Data1/Data0, Clock/Data, Supervised and Unsupervised F2F and OSDP-compatible RS-485 readers and keypads
- Supports Open Supervised Device Protocol (OSDP) readers, including biometric template transfer and Secure Channel encryption
- Downloadable firmware
- Six Form-C 5 A at 28 VDC relay outputs
- Up to 16 different formats
- Issue code support for magnetic and Wiegand formats
- Door contact supervision (open/closed)
- REX push-button monitor
- Strike control output
- Bi-colour reader status LED support and 2-wire LED support
- Beeper control
- Dedicated tamper and power failure circuits
- Support for offline reader access mode
- On-board jumpers for termination
- On-board regulator allows 12 VDC reader support from 24 VDC power source
- DIP switch-selectable addressing
- Advanced Encryption Standard (AES) 128-bit or 256-bit encryption supported, depending on ISC and OnGuard version
- Supports Schlage® Handkey® template download
- Compatible with current and previous versions of OnGuard Extended Functionality
- Connect FIPS-201 readers for embedded authentication (when used with LNL-4420 and appropriate HID® and OnGuard software and licenses)

LNL-1320-S3

Dual reader interface module

Technical specifications

System

Controller type	Reader module
Software compatibility	OnGuard
Max. no. of card formats	16
PCB only	Yes

Readers / doors

Max. no. of doors	2
Max no. of readers	2

Interfaces

Reader interface	Clock-data, OSDP, Wiegand
Host connection	RS485

Inputs / outputs

Max no. of outputs	6 outputs, Form-C contacts: Normally Open (NO) Contact: 5 A @ 30 VDC, Normally Closed (NC) Contact: 3 A @ 30 VDC
Inputs	8 unsupervised/supervised, standard EOL: 1k/1k ohm, 1% 1/4 watt
Inputs	2 unsupervised, dedicated for cabinet tamper and UPS fault monitoring

Electrical

Operating voltage	12 to 24 VDC \pm 10%, 550 mA max. (plus reader current) 12 VDC @ 550 mA (plus reader current) max., 22.5 BTUs 24 VDC @ 330 mA (plus reader current) max., 27.0 BTUs
Power supply type	VDC

Physical

Physical dimensions	152 x 203 x 25 mm
Net weight	312 g

Environmental

Operating temperature	0 to +70°C
Storage temperature	-55 to +85°C
Relative humidity	5 to 95% noncondensing

Regulatory

Compliance	CE, FCC, RoHS, UL 1076, UL 294
Standards	FCC Part 15, ULC CSA-C22.2, CAN/ULC-S319-05, cUL/ORD-C1076



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 March 2024 - 10:37