

## LNL-CK

### **Command Display terminal Lenel Command Keypad - 32-character back-lit LCD display with a 16-position keypad, supports both direct RS-485 communication with the ISC and Wiegand**

The LNL-CK Lenel Command Keypad integrates a 32-character backlit LCD display with a 16-position keypad and a reader port. The command keypad serves as a command reader, a reader from which user commands can be issued to execute local I/O functions. Reader command programming is accomplished using the OnGuard System Administration application.

The LNL-CK display indicates time in either 12 or 24-hour clock format. The format is automatically chosen based on the regional settings of the computer on which the Communication Server is running. The LNL-CK display also provides command status and other text feedback during reader operations. For example, when performing the Extended Held Open command, the LNL-CK displays the countdown time before the Held Open time is reached, as well as basic intrusion arm/disarm functions.

The LNL-CK communicates with the Lenel Intelligent System Controller (ISC) either through direct, multidrop, 2-wire RS-485 communication to the ISC, or through a reader port of a Lenel Dual Reader Interface Module (LNL-1320).

The LNL-CK may be configured in one of three ways: as a stand-alone RS-485 device, as an alternate reader to a primary reader, or as a reader device connected to the Wiegand input of a LNL-1320. In any of these modes, an optional reader with a Data1/Data0 or clock/data output may be connected to the LNL-CK to provide Card Only, Card or PIN, or Card and PIN capability.



### **Details**

- 32-character backlit LCD display
- 16-position keypad with 4 function keys
- Supports all "approved for use" reader technologies from Lenel that communicate using Data1/Data0 or clock/data communication
- Arm, Disarm, Bypass and Force Arm alarm mask groups
- Extended Held Open Time via Command Keypad with feedback
- Reader command support
- Reader command support
- Supports reader mode changes by Timezone control
- Supports PIN mode on LNL-CK keypad. With optional reader, all other modes are also supported
- Ability to adjust backlight on/off times
- Flash upgradable firmware
- Built-in DIP switch selectable RS-485 termination

# LNL-CK

**Command Display terminal Lenel Command Keypad - 32-character back-lit LCD display with a 16-position keypad, supports both direct RS-485 communication with the ISC and Wiegand**

## Technical specifications

### Technology

Reader type	LCD display
-------------	-------------

### Interface & connections

Interface	RS-485, Wiegand
-----------	-----------------

### Operation

PIN keypad	Yes
------------	-----

### Electrical

Power supply type	VDC
Power supply value	12 VDC
Current consumption	175 mA

### Physical

Physical dimensions	172 x 127 x 25 mm
Net weight	400 g
Colour	White
Form factor	Oversized
Mounting type	Surface mount
Color	White
Dimensions	6.75 x 5.00 x 1.0 in. (172 x 127 x 25 mm)
Weight	14 oz. (400 g) nominal
Mounting	Surface-mount or 3-gang box

### Environmental

Operating temperature	0 to 50°C
Storage temperature	-20 to +70°C
Relative humidity	0% to 95% noncondensing
Operating Temperature	32° to 122° F (0° to 50° C)
Storage Temperature	Storage: -4° to 158° F (-20° to 70° C)
Humidity	0% to 95% RHNC

### Regulatory

Compliance	CE, FCC, UL
------------	-------------

### Primary Power

Voltage	12 VDC +/- 15%
Current	175 mA terminal only

### Reader

Power	Pass-through (non-regulated)
LED Control	2-wire or 1-wire bicolor LED
Buzzer Control	Available with 1-wire LED control
Interface	2-wire RS-485, or Wiegand

### Technology

Communication	RS-485: up to 4000 ft. (1219 m) max, 24 AWG, 100 ohm impedance Wiegand: up to 500 ft. (152 m) max, 18 AWG stranded wire
---------------	---

### Approvals

FCC approved, UL-listed, CE-marked
------------------------------------



The latest product specifications can be located at [www.lenel2.com](http://www.lenel2.com) or by contacting your sales representative.

LenelS2 reserves the right to change product specifications without prior notice.

Last updated on 29 March 2024 - 11:21