

LNL-KEYS

2x Spare keys for LNL-300XA and LNL-600XA

Product Overview

The new LenelS2 access control range of switch mode power supplies has been specifically designed to house all common LenelS2 access control door controllers & modules.

With different power options and enclosure sizes the range provides a solution for up to a 12 LenelS2 controllers/modules (refer to the manual for all the different combinations). The modular construction simplifies maintenance.

All PSU models offer fault signalling and can charge a 12 VDC standby battery to provide backup power on a mains failure. Multi-fused outputs are provided to allow the installer to protect individual circuits as required. All models possess a mains fail relay output while the LNL-200XA, LNL-300XA and LNL-400XA models also offer additional Battery Monitoring and Deep Discharge Protection to prevent premature battery failure when operating in standby mode for extended periods.

The LNL-300XA and LNL-600XA is provided with a unique hinged cabling system whilst also offering an independent ancillary relay that can be used for applications such as a 'Fire' door release relay. The LNL-600XA can provide either 12 VDC or 24 VDC.

The products use energy efficient switch mode technology and therefore have a universal mains supply input (90 to 264 VAC).

Ultra PoE Splitter with 12 VDC Standby Battery Functionality

Save time and money with the Ultra PoE powered PSU - the unique PoE powered device that provides power for critical IP systems such as Access Control, over a single Ethernet cable. The Ultra PoE powered PSU is a unique PoE powered device that can charge from 12 VDC 7/8 Ah up to 17/18 Ah batteries whilst continuing to provide a 13.8 VDC output of up to 3 A.

If the PoE power being provided to the input fails, the battery seamlessly takes over continuing to provide the 13.8 VDC voltage to the device.

Available as a DIN mountable module, and it can be used in a variety of PoE applications such as CCTV or Access control.



Details

- Fits in the following enclosures : - LNL-300XA - LNL-300XA-ENC - LNL-300UL-ENC - LNL-600XA - LNL-600XA-ENC
- 3 Year warranty

LNL-KEYS

2x Spare keys for LNL-300XA and LNL-600XA

Technical specifications

General

Network monitoring	No
--------------------	----

Electrical

Power supply type	Accessories
-------------------	-------------

Physical

Physical dimensions	94 x 66 x 33 mm
Net weight	70 gr
Shipping weight	75 gr
Mounting type	Clip on

Environmental

Environment	Indoor
Operating temperature	-10 to +40°C
Storage temperature	-20 to +80°C

How to order

LNL-FUSE-4	4-Way Fused Output Module with LED's(=LNL-300XA-PSUFOM4), with LNL-300XA-ENC enclosure (437 x 245 x 110 mm) and includes cable guide support for LNL boards, including front and pryoff tamper - CE marked (key and screw locked)
LNL-FUSE-8	8-Way Fused Output Module with LED'sincludes front and pryoff tamper (cable guide not included), key locked. Fits a LNL-200XA-PSU, LNL-200XA-U-PSU, LNL-300XA-PSUFOM4, LNL-400XA-PSU
LNL-FUSE-12FOM4	4-Way Fused Fire Output Module with LED's (12VDC) and individual Fire Relay functionality - CE marked
LNL-FUSE-12FOM8	8-Way Fused Fire Output Module with LED's (12VDC) and individual Fire Relay functionality - CE marked
LNL-FUSE-12FOM12	12-Way Fused Fire Output Module with LED's (12VDC) and individual Fire Relay functionality - CE marked
LNL-KEYS	2x Spare keys for LNL-300XA and LNL-600XA
LNL-CONDUIT	2x 500 mm self-adhesive 20 mm conduit lengths for the LNL-300XA-ENC
LNL-300XA-LOCKSET	2x Spare keys with 1x lock for LNL-300XA enclosure
LNL-600XA-LOCKSET	4x Spare keys with 2x locks for LNL-600XA enclosure