



LNL-PR10-C

Proximity Mini-Mullion Reader: Compact proximity reader, designed to fit in small spaces, or to be mounted to a door mullion; CREAM ; Wiegand interface



LNL-PR10-C

Proximity Mini-Mullion Reader: Compact proximity reader, designed to fit in small spaces, or to be mounted to a door mullion; CREAM ; Wiegand interface

Technical specifications

System

Max. reader distance to panel 152 m

CSN (Card Serial Number) Yes

Technology

Reader type Proximity

Reader operating-transmitting frequency 125 KHz

Supported technology AWID Prox, GE ProxLite/CASI Prox, HID Prox, 125 kHz LenelProx®, Schlage Proximity

Interface & connections

Interface Wiegand

Operation

PIN keypad No

Electrical

Current consumption 65 mA

Physical

Physical dimensions 108 x 44 x 21 mm

Net weight 116 g

Colour Cream

Material PBT Polymer

Form factor Mini-Mullion

Mounting type Surface mount

Environmental

Environment Outdoor

Operating temperature -35 to 67°C

IP rating IP65

Regulatory

Compliance CE, FCC, IC, UL 294



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 March 2024 - 11:32