

# NC-BA-SM-W

## Conventional base accessory - Surface mount (White)

### General

---

The NC-BA-SM-W is an NC-Series surface mount base accessory. It allows cabling to be installed by running standard electrical conduit directly into the base, leaving no exposed cabling.

### Preparation

---

The standard rear cable entry into the base is available with the same wide opening dimensions to the standard base with ample room for cables. In addition, four entry points are provided on the wall of the fixture to accommodate side entry, spaced at 90° around the base to allow entry and exit in all directions.

### Installation

---

The conduit entry points are conveniently supplied with breakouts. Keyhole screw fixing locations adds to the ease of installation.

The standard NC-Series detector base fits snugly on top of the fixture, completing the installation with the same feature set as for standard surface mount installation for quick, easy and secure detector placement.



### Details

---

- Large rear cable entry with ample space for cables
- Side conduit entry protects cables from damage
- Breakout support for conduit entry
- Installation fixture with first fix screw option reduces installation time and effort
- Allows surface cabling for all NC-Series conventional detector bases

# NC-BA-SM-W

## Conventional base accessory - Surface mount (White)

### Technical specifications

#### General

|               |                                |
|---------------|--------------------------------|
| Compatibility | NC-Series point detector bases |
|---------------|--------------------------------|

#### Physical

|                       |                              |
|-----------------------|------------------------------|
| Physical dimensions   | 101 x 25 mm (Ø x D)          |
| Net weight            | 23.5 g                       |
| Colour                | Traffic white (RAL9016)      |
| Mounting type         | Ceiling mount                |
| Cable entries         | 5                            |
| Conduit specification | M16 or M20 (16 or 20 mm (Ø)) |
| Material (body)       | ABS-757K-NC                  |

#### Environmental

|                       |                         |
|-----------------------|-------------------------|
| Vandal proof          | No                      |
| Operating temperature | -10°C to +65°C          |
| Storage temperature   | -30°C to +75°C          |
| Relative humidity     | 10 to 93% noncondensing |
| Environment           | Indoor                  |

#### Regulatory

|                     |                         |
|---------------------|-------------------------|
| Compliance          | CE, REACH, RoHS 2, WEEE |
| Certification marks | CE, UKCA                |

#### Compatible products

| Category         | Reference | Description                                                  |
|------------------|-----------|--------------------------------------------------------------|
| Detection device | NC-DB-B   | Conventional standard point detector base (Black)            |
| Detection device | NC-DB-W   | Conventional standard point detector base (White)            |
| Detection device | NC-DB2R-W | Conventional dual relay base (White)                         |
| Detection device | NC-DBD-W  | Conventional standard point detector base with diode (White) |
| Detection device | NC-DBR-W  | Conventional relay base (White)                              |

