



OH2000E-RO-220

Osborne-Hoffman receiver

Overview

The Osborne-Hoffman receiver OH2000E-RO-220 is a high capacity rack mount receiver able to receive up to 8 add-on cards (PSTN or TCP/IP line cards).

Each new cards can be installed in a few second by opening the front panel and simply sliding the cards in. This can even be done while the receiver is powered.

This receiver supports all common protocol except XSIA, CESA and Telim as input but only supports the proprietary Osborne-Hoffman protocol as automation output.



Details

- Leading edge Central Station Monitoring Receiver
- Industry standard since 1981
- Using Digital Signal Processing to decode received signals from PSTN or TCP/IP Line cards
- Easy to install
- Up to two TCP/IP Line cards for support of maximum 6000 accounts
- Up to eight 2-Lines PSTN cards for maximum 16 PSTN lines
- Front loading and hot swapping of cards
- Non-volatile RAM with no internal battery
- Stores 12.000 past events in memory, retrievable any time
- 32-character, 2-line LCD display
- Serial RS232 port for programming and updates
- Parallel external printer port

OH2000E-RO-220

Osborne-Hoffman receiver

Technical specifications



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 23 July 2021 - 10:29