

PB30

3 m, 180° AIR Beam Tower (single sided) including installation kit

Pillar packing list

1. Top/bottom cover : 2 pcs
2. Polycarbonate cover : 2 pcs
3. Aluminium profile : 1 pcs
4. Tamper plate : 1 pcs (EP1)
5. Tamper : 1 pcs (EP1)
6. M3 DIN 934 : 2 pcs (EP1)
7. M3x16 DIN 84 : 2 pcs (EP1)
8. M4x8 DIN 84 : 4 pcs (EP3)
9. M4x20 DIN 933 : 2 pcs (EP2)
10. M4 DIN 934 : 16 pcs (EP3) (C3)
11. M4 DIN 985 : 2 pcs (EP2)
12. M4 DIN 125 : 2 pcs (EP2)
13. Spacer : 2 pcs (EP2)
14. Cable gland PGM16 : 1 pcs (EP3)
15. Cable gland PGM20 : 1 pcs (EP3)
16. M8x16 DIN933 : 6 pcs (TA4)
17. Side bracket >2m : 2 pcs
18. M8 DIN 985 : 6 pcs (TA4)
19. M8 DIN 125 : 6 pcs (TA4)
20. M4x12 DIN 7985 : 12 pcs (C3)
21. Bracket : 6 pcs
22. dia.2.9x16 DIN 7981 : 12 pcs (C3)
23. Anchor bolt : 4 pcs (MAN2) and 1 Coupling.



Details

- 3m height
- 180° view
- CE certified product

PB30

3 m, 180° AIR Beam Tower (single sided) including installation kit

Technical specifications

General

Accessory group	Perimeter / Outdoor
Type	Mounting

Electrical

Operating voltage	12 to 24 V
-------------------	------------

Physical

Physical dimensions	2970 x 130 x 150 mm (H x W x D)
Net weight	8.55 kg
Material	ABS plastic, Aluminium

Environmental

Operating temperature	-15 to 50°C
-----------------------	-------------

Detection

Angle of view	180°
---------------	------

Output

Tamper switch	CO (change over)
---------------	------------------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.