

PCG-N Graphics package network application with copy protection key

General

The graphical packages provide the users with a graphical front end to visualise the alarms occurring at the panel, to take actions on the panel, to log and acknowledge the alarms on the PC.

The package's library includes a wide selection of objects (icons). Th epackage imports bmp & wmf drawings from virtually any package. The different icons can be placed in different layers in order to open the package to different disciplines like access control, intrusion, CCTV etc. Programming is done by simple copy-paste and drag & drop commands. Configuration menus are password protected.

The packages allow multiple operators with password and alias log-on.

Operators can be assigned up to 4 configure levels.

The software visualises; alarms, pre-alarms, faults, and conditions per point.

Also status changes in inputs and outputs can be monitored onscreen. Fire alarms are to be acknowledged.

The graphics consist of front, top and floor plan views. A certain amount of plans and extra information pages are available for each panel. To save precious programming time and avoid mistakes, the sensor's text information is supplied directly from the panels.

Used with FP2000 the package allows to visualise the real time statistical information kept for each sensor. Selecting any panel's loop visualises all its addresses, types and condition.

As the system allows bi-directional communication, any output anywhere on the network can be triggered by a simple click on the screen buttons. Several navigation buttons can be created to easily move around the building.

For larger applications, a TCP/IP client-server version can be installed or upgraded from PCG-S or PCG-N.



Details

- Provide bi-directional communication with single fire panels and networked fire systems, both locally and remote via modem
- Windows 2000 and NT compatible
- For use with FP2000, FP1200, FP1100 and FP700
- Constructed around Sybase SQL Anywhere
- Large selection of icons
- Visualises inputs & outputs
- Information page per point
- · Get texts from panel
- Several operator levels and passwords
- Operator configurable
- Multiple navigation buttons
- Event logs
- Basic drawing package included
- · Imports .bmp & .wmf drawings from virtually any package
- · Hardware key protected

The software has numerous consulting and retrieving capabilities.

The package conforms to pr EN 50137-1.

The program is protected by means of a software protection key.

PCG-N Graphics package network application with copy protection key

Technical specifications	
Processor	
	Pentium II 266 MHz (or better)
RAM	
	64 Mb (or more)
Display adapter	
	SVGA or better
Hard disk space	
	200 MB
Pointing device	
	MS Mouse, Bus or P/S2
Graphical environment	
	Windows NT
Communication ports	
	1 x RS-232 - Depending on drivers
	1 x Parallel - Printer port (for key)



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.