

SH-51-0100-0001-99

SmartCell Fire Manual Call Point

Overview

The SmartCell Call Point is quick and easy to install and offers individual addressing at the Excellence Control Panel or Gateway.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the Excellence wireless gateway.



Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism

SH-51-0100-0001-99

SmartCell Fire Manual Call Point

Technical specifications

General

Status indication	LED
Wireless frequency	868 MHz
Compatibility	Excellence Gateway

Electrical

Batteries	2 x 3.6 V lithium thionyl chloride batteries Fanso: ER14505M HCB: ER14505M (HCB-JS-TZ-02-547)
-----------	---

Physical

Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor

Regulatory

Compliance	CE, REACH, RED (2014/53/EU), RoHS 3, WEEE
Certification	CPR
Standards	EN54-11 EN54-13 EN54-25

Compatible products

Category	Reference	Description
Batteries	SH-836-000	AA ER14505M 3.6V Lithium Battery
Interface unit	SH-14-3201-000 1-99	Excellence SmartCell Addressable Wireless Gateway
Test Equipment	SH-51-BASE-010 0	SmartCell Manual Call point - Base Red (10 pack)