

# SMA-L-PROX

**MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE**

## **MA SIGMA Lite & MA SIGMA Lite Plus Series**

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door Mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

## **Embedded web server**

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tablet, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

## **Enhanced interactivity**


Thanks to the 2.8" QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

## **Compatible with existing installations**

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioScrypt network.

## **Enhanced security features**

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.



## **Details**

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, iCLASS or MIFARE/DESFire contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

# SMA-L-PROX

MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE

## Technical specifications

### System

Max. reader distance to Ethernet: 100 m, RS485: 1219 m panel

RTE (Request To Exit) No

CSN (Card Serial Number) Yes

Custom data model No

No. of LEDs 1

### Technology

Reader type BioMetric

Reader operating-transmitting frequency 125 KHz

Supported technology HID Prox 125 kHz

### Biometric

Biometric type Fingerprint

Biometric sensor type Optical

### Interface & connections

Interface Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand

Connector type Network, Pigtail

Pigtail length 40 cm

### Tamper type

Pry-off tamper No

Opening tamper Yes

### Operation

Stand-alone Yes

PIN keypad No

### Electrical

Power supply type VDC

Power supply value 12 to 24 VDC

### Physical

Net weight 280 g

Shipping weight 325 g

Colour Black

Material Polycarbonate

Form factor Oversized

Mounting type Surface mount

### Environmental

Vandal proof No

Storage temperature -10 to +55°C

### Regulatory

Compliance CE, FCC, REACH, RoHS

