



# SPB-2R

## Plug-in Base, RED

### General

---

The SPB-2R is a RED, first fix plug in base for the ZP755 and EA55 series sounders and sounders with visual indicators.

### First fix wiring option

---

The SPB-2 plugable bases provide a basis for terminating ZP755 and EA series loop wiring at first fix stage. Forming an integral part of the overall unit assembly, the bases are provided with slots for screw fixing, either directly to the building structure, or a wide range of international conduit boxes. Bases feature large wiring terminals with captive clamping washers to ensure secure termination.

### Robust manufacture

---

Bases are manufactured in molded ABS and are also available in grey, polar white and white.



### Details

---

- First fix facility
- Ease of installation
- Large wiring terminals

# SPB-2R

## Plug-in Base, RED

### Technical specifications

#### General

|               |                                   |
|---------------|-----------------------------------|
| Compatibility | ZP755 & EA55 notification devices |
|---------------|-----------------------------------|

#### Electrical

|                   |                          |
|-------------------|--------------------------|
| Operating voltage | 16 - 22 VDC (Loop power) |
|                   | 24 VDC (External power)  |

#### Physical

|                     |                            |
|---------------------|----------------------------|
| Physical dimensions | 127 x 5 mm (Ø x H)         |
| Net weight          | 61 g                       |
| Colour              | Red                        |
| Mounting type       | Surface mount              |
| Material            | Moulded ABS                |
| Terminals           | Loop +ve in/out            |
|                     | Loop -ve in/out            |
|                     | Cable screen continuity    |
|                     | 24 VDC +ve external supply |
|                     | 24 VDC -ve external supply |

#### Environmental

|                       |                         |
|-----------------------|-------------------------|
| Vandal proof          | No                      |
| Operating temperature | -10°C to +75°C          |
| Storage temperature   | -10°C to +75°C          |
| Relative humidity     | 20 to 95% noncondensing |
| Environment           | Indoor                  |

#### Regulatory

|            |    |
|------------|----|
| Compliancy | CE |
|------------|----|

#### Compatible products

| Category            | Reference | Description                                     |
|---------------------|-----------|-------------------------------------------------|
| Notification device | 177401    | ZP755R-2R room sounder C/W cover                |
| Notification device | 177601    | ZP755HA-2R omni sounder, red                    |
| Notification device | 178001    | ZP755HAV-2R horn sounder, visual indicator, red |