SPB-2R

Plug-in Base, RED

General

The SPB-2R is a RED, first fix plug in base for the ZP755 and EA55 series sounders and sounders with visual indicators.

First fix wiring option

The SPB-2 plugable bases provide a basis for terminating ZP755 and EA series loop wiring at first fix stage. Forming an integral part of the overall unit assembly, the bases are provided with slots for screw fixing, either directly to the building structure, or a wide range of international conduit boxes. Bases feature large wiring terminals with captive clamping washers to ensure secure termination.

Robust manufacture

Bases are manufactured in molded ABS and are also available in grey, polar white and white.

Details

- First fix facility
- Ease of installation
- Large wiring terminals

SPB-2R
Plug-in Base, RED

Technical specifications

General

Compatibility	ZP755 & EA55 notification devices

Electrical

Operating voltage	16 - 22 VDC (Loop power) 24 VDC (External power)

Physical

Physical dimensions	127 x 5 mm (Ø x H)
Net weight	61 g
Colour	Red
Mounting type	Surface mount
Material	Moulded ABS
Terminals	Loop +ve in/out
	Loop -ve in/out
	Cable screen continuity
	24 VDC +ve external supply
	24 VDC -ve external supply

Environmental

Vandal proof	No
Operating temperature	-10°C to +75°C
Storage temperature	-10°C to +75°C
Relative humidity	20 to 95% noncondensing
Environment	Indoor

Regulatory

Compliancy	CE

Compatible products

Category	Reference	Description
Notification device	177401	ZP755R-2R room sounder C/W cover
Notification device	177601	ZP755HA-2R omni sounder, red
Notification device	178001	ZP755HAV-2R horn sounder, visual indicator, red

KIDDE COMMERCIAL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 January 2026 - 12:29