

TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

General

The TESTIFIRE-ADAP is a specialist adaptor to replace the standard membrane on a Testifire XTR2 test cup. It enables functional testing of aspirating smoke detection systems. It can also be used to test flat/flush detectors.



Details

- Fits to Testifire XTR2 in place of standard membrane
- Allows placement around ASD pipe and alignment with sampling hole
- Also suitable for use with flat or flush mounted detectors

TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

Technical specifications

Physical

Colour	Black
--------	-------

Environmental

Vandal proof	No
Operating temperature	5 to 45°C (41 to 113°F)
Storage temperature	-10 to 50°C (14 to 122°F)
Relative humidity	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
------------	-------------------------

SKU info

Product brand	testifire
---------------	-----------

Compatible products

Category	Reference	Description
Test Equipment	TESTIFIRE-XTR2	All-in-one connected smoke/heat detector test kit
Test Equipment	TESTIFIRE-XTR2-6M	All-in-one connected smoke/heat detector test kit to 6 m
Test Equipment	TESTIFIRE-XTR2-HEAD	All-in-one connected smoke/heat detector test head



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.