

TESTIFIRE-XTR2-6M

All-in-one connected smoke/heat detector test kit to 6 m

Powerful insights, automated test reports & records

The Testifire-XTR2 combines testing and reporting to deliver on compliance, giving service companies and building owners the insight and assurance they demand. The Testifire-XTR2 is designed to work with all detector brands and models, and with both addressable and conventional systems.

Test modes

The Testifire-XTR2 supports all-in-one smoke and heat testing including smoke only, heat or hi-heat only, combined and sequential smoke/heat as well as ASD test compatibility.

DT Connect App

Every Testifire-XTR includes a 6-month trial of DT Connect premium. When the 6-month trial period ends, a DT Connect subscription is needed to continue accessing the full range of features. The Testifire-XTR2 can also be used without subscription, albeit with limited features.

DT Connect alongside the Testifire-XTR2, allows advanced features to streamline the testing process, easily manage site assets and optimise reporting capability by automatically generating test reports.

DT Connect allows for:

- Minimising time spent on basic tasks
- Panel time logging to synchronise test and panel event timestamps *
- Test result capturing
- Asset identification *
- Panel reconciliation *
- Job summary
- Shareable reports *

* Premium DT Connect features

Product information

The Testifire-XTR2 kit includes:

- 1 x TESTIFIRE-XTR2-HEAD
- 1 x TESTIFIRE-BP Li-ion Battery
- 1 x TESTIFIRE-GEN Smoke Generator
- 1 x TESTIFIRE-CHAK Charger Kit
- 1 x TES3 Smoke Cartridge
- 1 x ET010 Fibre-glass telescopic pole 4.5 m
- 1 x FG010 Universal removal tool on swing frame
- 1 x CB001 Carrying bag



Details

- Rapid smoke generation saves waiting time
- 50% faster heat and hi-heat activation compared with the legacy TM010
- Sequential & combined test modes including hi-heat testing up to 100°C
- TFT-LCD full colour touch screen user interface
- Automatic LED torch in dark environments
- Automatic test result capture with detector LED recognition support
- Clearing mode to prevent re-alarms
- Robust and repairable
- Bluetooth enables communication to the DT Connect App with 6-month free PREMIUM support
- Optional subscription for premium features in the DT Connect app and Cloud Portal

TESTIFIRE-XTR2-6M

All-in-one connected smoke/heat detector test kit to 6 m

Technical specifications

Electrical

Power supply type	Batteries
Operating voltage	10.8 V (35.1 wh / 3250 mAh)
Current consumption	< 0.5 A rms (smoke testing) 4 to 6 A rms (heat testing)
Battery type	Lithium Ion
Charging	USB-C connection to charging cradle

Physical

Physical dimensions	406 x 156 x 150 mm
Net weight	1.25 kg
Shipping weight	2.39 kg
Colour	Black, Grey
Stimulus type	Cartridge

Environmental

Vandal proof	No
Operating temperature	5 to 45°C (41 to 113°F) - Head unit 5 to 40°C (41 to 104°F) - Charger cradle
Storage temperature	-10 to 50°C (14 to 122°F)
Relative humidity	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Regulatory

Compliance	CE, REACH, RoHS 3, WEEE
Certification	CE

SKU info

Product brand	testifire
---------------	-----------

Test

Carbon Monoxide	No
Heat	Yes
Smoke	Yes

Compatible products

Category	Reference	Description
Test Equipment	ET011	Fibreglass Extension Tube 1.2 m
Test Equipment	TES3-6PACK	XTR2 Replacement smoke cartridge - pack of 6
Test Equipment	TESTIFIRE-ADAP	XTR2 Adaptor for aspiration and flat detectors
Test Equipment	TESTIFIRE-MEM	XTR2 Replacement membrane ø 90 mm
Test Equipment	TESTIFIRE-MEML	XTR2 Large detector membrane ø 122 mm
Test Equipment	TESTIFIRE-SOP	XTR2 Replacement stand-off plate