

TVD-5408

TruVision IP Outdoor Dome Camera, H.265/H.264, 5.0MPX, 2.8 to 12 mm motorized lens, DWDR, True D/N, 30 m IR, audio, alarm, BNC, micro SD/SHDC slot, Intelligence, POE

Overview

The TruVision line of IP dome form factor cameras leverages the latest H.265 video compression technology to bring state-of-the-art, high-definition pictures to the mass video surveillance market. With camera resolutions of 2, 3, or 5 megapixel, these IP cameras represent a flexible video surveillance device to meet any need. Equipped with advanced technology and signal processing capability, they effectively capture video under challenging conditions.

TruVision cameras utilize H.264 and/or H.265 compression technology with triple-streaming capability, making it easy to manage the camera's bandwidth usage. Motorized varifocal lens technology allows the user to remotely adjust the varifocal lens length and focus the camera with the touch of a button. Select models feature Super Low Light technology, which provides a clear image in low lighting conditions with a minimum of "grainy" interference. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.

These cameras go above and beyond standard motion detection with enhanced alarm capabilities, including cross lines, intrusion, de-focus and face detection features. Each is user-configurable to best suit the installation environment. A Region of Interest function ensures specific portions of an image are given priority during instances of high network traffic or network degradation.

Location-specific functions include a Hallway View Mode to provide a portrait view of a hallway or corridor, a De-Fog Mode to help resolve images through fog or rain and Electronic Image Stabilization for installations subject to physical vibration or shaking.



Details

- Maximum Resolution: 2592 × 1944
- Maximum Real Time Resolution: 2592 × 1944 @ 25 fps
- Designed to PSIA and ONVIF Profile G and S open standards
- H.265 and/or H.264 compression with triple-streaming functionality
- Edge recording up to 128GB SDHC card
- 1/1.8" CMOS image sensor
- Motorized IR Cut Filter
- Color: 0.01 Lux @f1.2 (AGC On), 0 Lux IR On
- Motorized Lens 2.8 to 12 mm
- Up to 30m IR illumination
- Digital Wide Dynamic Range
- Intelligence (Face detection, Audio Exception Detection, Intrusion Detection, De-focus Detection, Region of Interest (ROI), Electronic Image Stabilization (EIS), Defog, Scene Change Detection, Cross Line Detection, Advanced Motion Detection, Region Entrance Detection, Region Exit Detection, Object Removal, Object Left Behind, Object Counting)

TVD-5408

TruVision IP Outdoor Dome Camera, H.265/H.264, 5.0MPX, 2.8 to 12 mm motorized lens, DWDR, True D/N, 30 m IR, audio, alarm, BNC, micro SD/SHDC slot, Intelligence, POE

Technical specifications

General

Technology	IP
Video standard	NTSC, PAL
Image settings	Hallway View, Mirror, ROI (Region Of Interest)
Video output	BNC Composite PAL / NTSC
Software compatibility	OnGuard, Prism, TruVision Navigator, TVRmobile, Web Browser

Camera

Sensor size	1/1.8"
Max. resolution	5 MP
Sensor scan	Progressive
Sensor type	CMOS
Total Pixels (H x V)	2688 x 1520
Effective pixels (H x V)	2688 x 1520
Digital S/N ratio	52 dB (AGC OFF)
Shutter time	50 Hz: 1/3s to 1/100,000s
IP Compression/Standard	H.265/ H.264 / MJPEG
Maximum Resolution (@ 2592 x 1944 @ 25 fps FPS)	
Maximum Real Time Resolution (@ FPS)	50Hz: 25fps(2592 x 1944, 2560 x 1920, 2048 x 1536) 50fps(1920 x 1080, 1280 x 960, 1280 x 720) 60Hz: 30fps (2592 x 1944, 2560X1920, 2048 x 1536), 60fps(1920 x 1080, 1280 x 960, 1280 x 720)"
Multiple Streaming	Triple Streams
Video Bit Rate	128 Kbps to 16 Mbps, adjustable
Composite Output (BNC)	PAL, 1.0 Vp-p @ 75 ohm

Lighting performance

WDR type	Digital WDR
Digital noise reduction	3D DNR
Day/night	True Day/Night
Motorized IR cut filter	Yes
Color sensitivity	0.01 Lux @ (F1.2, AGC ON)
B/W sensitivity	0 lux with IR on
Infrared (IR)	Yes
IR sensitivity	0 lux with IR
IR range	Up to 30 m
IR wavelength	850 nm
Highlight compensation (HLC)	No

Encoding

Sub stream compression	H.264, MJPEG
Video bit rate	128kbps to 16Mbps
Main stream resolutions	2688 x 1520
Sub stream resolutions	176 x 144 (QCIF), 352 x 288 (CIF), 704 x 576 (4CIF)
Max. resolution @ fps	2592 x 1944 @ 25 fps

Lens

Lens type	Varifocal motorized
Focal length	2.8 to 12 mm
Auto iris	Yes
Auto focus	Yes
Motorized zoom	Yes
Control type	DC

Network

Integration	CGI, ONVIF, PSIA
Supported network protocols	802.1x, DDNS, DHCP, DNS, ezDDNS, FTP, HTTP, HTTPS, IPv4, IPv6, NTP, PPPoE, QoS, RTP, RTSP, SMTP, SNMP, TCP/IP, UPnP
PoE IEEE	802.3at
Standard & Integration	ONVIF Profile (G,S), PSIA, CGI

Audio

Audio compression	G.711, G.722.1, G.726, MP2L2
Audio in	1
Audio out	1

Alarm I/O

Alarm inputs	1
Alarm outputs	1
Alarm I/O connection	Terminal Type

Storage

Local storage support	Yes
Local storage type	Built-in Micro SD/SDHC/SDXC card slot
Max. SD card capacity	128 GB

Video intelligence

Alarm trigger	Motion detection, Privacy Masking, Video tampering
Smart event	Advanced motion detection, Audio exception detection, Defocus, Defog, Electronic Image Stabilization (EIS), Face detection, Intrusion detection, Line crossing detection, Object counting, Object left behind, Object removal detection, Region entrance detection, Region exiting detection, Scene change detection

Electrical

Power supply type	12 VDC, 24 VAC
Power consumption	17 W
Current consumption	1.420 A @ 12 VDC / 1.010 A @ 24 VAC
Voltage Input	12VDC / 24VAC / PoE (802.3af / 802.3at with heater)
Auxiliary Power	50mA @12VDC Line level

Physical

Physical dimensions	Ø 159.8 x 146 mm (6.29 x 5.75 in.)
Net weight	2.1 kg (4.62 lbs.)
Colour	Grey
Form Factor	Dome

TVD-5408

TruVision IP Outdoor Dome Camera, H.265/H.264, 5.0MPX, 2.8 to 12 mm motorized lens, DWDR, True D/N, 30 m IR, audio, alarm, BNC, micro SD/SHDC slot, Intelligence, POE

Environmental

Vandal proof	Yes
Impact rating	IK10
Environment	Outdoor
Operating temperature	-40 to +60°C with heater on -40 to +140°F with heater on
Storage temperature	-30 to 60°C (-22 to 140°F)
IP rating	IP66

Regulatory

Compliance	CE, FCC, HALT, REACH, RoHS, UL, WEEE
------------	--------------------------------------

LocalStorage


Input	Audio in / Mic in (line level)
Output	Audio out
Audio bit rate (protocol)	G.711ulaw, G.711alaw, MP2L2, G.726, PCM

Camera Alarm

Input/Output	1 input / 1 output
--------------	--------------------

Compatible products

Category	Reference	Description
Camera Housing	TVD-BS-5C	TruVision Dome Bubble Spare, Clear, for motorized lens domes
Camera Housing	TVD-BS-5S	TruVision Dome Bubble Spare, Smoked, for motorized lens domes



Unit: mm



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 January 2024 - 16:36