TVN-1004CS-1T

TruVision NVR 10, 4 channels, 4 channel PoE, 20 Mbps, 1TB

Overview

TruVision NVR 10c (TVN 10) is a plug-and-play entry-level network video recorder. It stands out because of its ease of use and straightforward plug-and-play camera network configuration. TVN 10 represents a highly flexible solution, available in a 4, 8 or 16 IP channel version – with and without camera PoE ports.

Plug & Play

Setting up TVN 10 is easy. Its embedded PoE ports allow you to connect IP cameras as they were analog cameras. When plugged in, cameras are automatically assigned IP addresses, are added to the recorder and set up to default configuration. Each IP camera can also be set up individually to ensure full flexibility.
Each plug & play port can be configured to provide no power, PoE-af or PoE-at to its connected IP camera. This setup can easily and intuitively be configured in the recorder's user interface.

Storage

TVN 10c features one embedded SATA port, allowing a maximum of 2TB onboard storage. As such, the unit is designed to provide 15 days of storage at HD @ 15fps on each channel. By lowering the resolution and frame rate or by changing the recording schedules, more days of storage can easily be achieved.

Local or remote operation

TVN 10 is designed to be flexible – not only in its deployment and product selection, but also in its day to day operations.
The unit can be fully controlled locally using the front panel buttons and mouse, displaying high resolution Full HD video on its local monitor VGA or HDMI video outputs. Alternatively, TVN 10 can be operated remotely using its full featured web browser interface or using the TruVision Navigator and TVRmobile software applications.



Details

- Up to 4 Plug & Play PoE ports
- Automatic setup of IP address, resolution & other settings through Plug&Play ports
- Up to 4 IP network cameras
- 20 Mbps for incoming streams
- PoE-af & PoE-at support
- Flexible PoE budgetting
- Up to 4 TB internal storage
- Up to 5 MPX resolution support
- HD & Full HD real-time support
- Start-up wizard for quick and easy installation
- ezDDNS
- H.264 & MPEG-4 dual streaming
- Reverse video playback
- Flexible bandwidth management
- HDMI&VGA video outputs
- Full set of front panel controls
- USB 3.0 support
- Compatibility with TruVision Navigator 5.0 SP2 and higher
- Compatible with TVRmobile for Android & iOS
- Compliant to the decree of August 3, 2007 defining the technical requirements of CCTV systems in France

TVN-1004CS-1T

TruVision NVR 10, 4 channels, 4 channel PoE, 20 Mbps, 1TB

Technical specifications

General

Technology	IP
Operating system	Embedded Linux
Rack mountable	No
Rack stacking size	1 U
Removable fan	No
Redundant power supply	No

Video / audio input

Camera channels	4
IP camera channels	4
Max. bandwidth per channel	16
Camera bandwidth	20
Max. IP audio in	4
Max. analog audio In	1
Supported video compression standards	H.264, MPEG-4
Supported video streaming standards	Onvif, PSIA, RTSP

Local viewing

HDMI output	1
HDMI version	1.4
VGA output	1
Max. local output resolution	Full HD 1080p

Remote viewing

Total available viewing bandwidth	40
Software compatibility	Advisor Management Software (ATS8600), MASterMind, OnGuard, TruPortal
Browser compatibility	Internet Explorer

Storage

Storage capacity	1 TB
SATA interfaces	1
Max. capacity per SATA HDD (TB)	2
Maximum recording resolution	6 MP
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Hard drive redundancy	No
Hard drive grouping	No
Hot swappable HDDs	No
SAS extension	No
Flip-open front panel	No
Auto archiving	No
Hot spare recorder	No
Edge failover recording	No

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Network ports per NIC	1
PoE ports	4
Total PoE budget	50
Max. PoE budget per port	30
Plug & Play PoE support	Yes
Flexible PoE allocation	No
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	No

External interfaces

USB interface back	1
USB interface front	1
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	48 VDC
Power consumption without HDD (W)	180

Physical

Physical dimensions	315 x 237 x 48 mm
Colour	Black

Environmental

Operating temperature	-10 to +55 °C
Relative humidity	10 to 90% noncondensing

Regulatory

Compliancy	CE, REACH, RoHS, UL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 August 2024 - 15:40