TVR-1204CHD-1T

TruVision DVR 12HD, HD Hybrid, 4 channel, 50% IP, 1TB

Overview


The TruVision DVR 12cHD (TVR 12cHD) is a cost-effective HD Hybrid video recorder capable of recording up to 4 camera inputs. This HD Hybrid recorder is uniquely qualified to upgrade existing analog installations, offering a competitive and practical solution for the market of HD analog, standard analog and hybrid recorders.

A true HD hybrid

Using the open HD-TVI technology, TVR 12cHD can connect any HD-TVI camera, offering HD and Full HD resolutions over existing coax cabling.
Next to HD-TVI, TVR 12cHD also connects standard analog cameras, allowing reuse of existing analog cameras which do not yet need to be replaced/upgraded.
Finally, TVR 12cHD is capable of connecting up to half of its total channels to TruVision IP cameras, making this a true HD Hybrid solution.

HD-TVI technology

HD-TVI allows you to run a Full HD analog signal over existing standard coax cabling, following the same specifications as for standard analog systems today. Additionally, TVR 12cHD allows you to access the local on-screen-display menu of TruVision HD-TVI cameras through over-the-coax control. This saves time in setup and facilitates maintenance afterwards.



Details

- Up to 4 analog cameras
- Up to 2 IP cameras (+2 analog)
- HD-TVI technology
- Over-the-coax control for TruVision HD-TVI cameras
- Use existing coax cabling for HD-TVI cameras
- Real-time HD recording
- Full HD recording at 12 fps
- Up to 2 TB internal storage
- Text overlay for POS/ATM
- Reverse video playback
- USB archiving
- Start-up wizard for quick and easy installation
- HDMI, VGA and BNC video outputs
- V-stream support
- Front panel controls
- Operations through OSD/browser/software
- TruVision Navigator support
- Mobile app for iOS, Android & Windows Mobile
- IP Keypad support
- ezDDNS

TVR-1204CHD-1T

TruVision DVR 12HD, HD Hybrid, 4 channel, 50% IP, 1TB

Technical specifications

General

Technology	HD-TVI analog
Operating system	Embedded Linux
Rack mountable	No
Rack stacking size	1 U
Removable fan	No
Redundant power supply	No

Video / audio input

Camera channels	4
Analog camera channels	4
IP camera channels	2
Max. bandwidth per channel	4
Max. IP audio in	2
Max. analog audio In	1
Supported video compression standards	H.264, MPEG-4

Local viewing

HDMI output	1
HDMI version	1.4
VGA output	1
BNC output	1
Max. local output resolution	Full HD 1080p
Synchronous playback OSD (channels)	Up to 4 channels
Reverse playback OSD (channels)	1

Remote viewing

Total available viewing bandwidth	60
Max. live viewing streams	128
Max. playback resolution web browser	1920 x 1080
Max. simultaneous playback web browser	Up to 4 channels
Reverse playback web browser (channels)	Up to 4 channels, depending on PC performance
Software compatibility	Advisor Management Software (ATS8600), MASterMind, OnGuard, TruPortal
Browser compatibility	Internet Explorer

Storage

Storage capacity	1 TB
SATA interfaces	1
Max. capacity per SATA HDD (TB)	2
Maximum recording resolution	Full HD 1080p
Recording modes	Alarm, Event, Manual, Time-lapse high, Time-lapse low
Hard drive redundancy	No
Hard drive grouping	No
Hot swappable HDDs	No
SAS extension	No
Flip-open front panel	No
Auto archiving	No
Hot spare recorder	No
Edge failover recording	No

Networking

Network interface cards (NIC)	1
NIC type	RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Network ports per NIC	1
DNS support	DDNS, ezDDNS, No-IP
HTTPS support	No

External interfaces

USB interface back	1
USB interface front	1
Serial interface	RS-232, RS-485
Alarm inputs	4
Alarm outputs	1
Max. analog audio outputs	1

Electrical

Operating voltage	12 VDC
Power consumption	10 W without HDD

Physical

Physical dimensions	315 x 237 x 48 mm
Net weight	less than 8kg without HDD
Colour	Black

Environmental

Operating temperature	-10 to +55 °C
Relative humidity	10 to 90% noncondensing

Regulatory

Compliancy	CE, REACH, RoHS, UL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 26 August 2024 - 15:40