

WU_06-66/T-EN54

Alu-style wall speaker 6W WU_06-66/T-EN54

Product overview

The 6W powered speaker is equipped with a 66mm full-range loudspeaker chassis and a 100V transformer with 3 power adjustments. The sturdy aluminium front panel provides a low resonance sound. Included is also a flush-mounted high-impact housing in black. For additional reliability, a 2 pin-ceramic block, a thermal fuse is provided and the speaker chassis is impregnated against wetness.

The speaker is also secured with the protection class IP 21C against the security risks of environmental influences.

The speaker is also compliant with the British Standard BS 5839, Part 8.

Quick and easy mounting with screws.

The speaker is also secured with the high protection class IP54 against the security risks of environmental influences. Quick and easy mounting with screws.



Details

- Wall-mounted aluminum-style speaker 6 W

WU_06-66/T-EN54

Alu-style wall speaker 6W WU_06-66/T-EN54

Technical specifications

Electrical

Power consumption	6 W
Output level	85 dB

Physical

Physical dimensions	120 x 120 x 102 mm (W x H x D)
Net weight	0.71 kg
Colour	Aluminium
Mounting type	Flush mount, Wall mount
Mounting position	Wall

Environmental

Operating temperature	-10 to +55°C
IP rating	IP21

Regulatory

Standards	EN54-24
-----------	---------



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.