

# 9-30709

## AirSense Stratos Standalone Command Module

### Description

---

AirSense Stratos Command Module provides a single location display, control and interfacing option for systems of upto 127 detectors. Command Module allows global programming of all detector functions simultaneously.

The integral bargraph automatically displays the status of the detector with the highest alarm level to identify potential problem areas.

The PIN protected programmer enables global entry of all detector settings to significantly reduce commissioning time.

### Typical Applications

---

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

### Options Available

---

- Addressable Protocol Interface Cards APIC™ available
- SenseNet compatible - up to 127 detectors per loop
- Remote Display units available
- Suitable for MatrixScan, a patented software system which provides virtual addressable location detection - e.g. 10 physical detectors would provide up to 45 unique addressable locations.



### Details

---

- RS485 communications built in as standard for networking and remote communications
- Network control of 127 detectors
- Built in Short Isolators for optimum reliability

# 9-30709

## AirSense Stratos Standalone Command Module

### Especificaciones técnicas

---

#### General

Indicación de estado	LED and LCD
Interfaz usuario	Keypad

#### Eléctrico

Voltaje de funcionamiento	21.6 to 26.4 VDC
Consumo de corriente	250 mA

#### Salida

Cantidad de salidas	5 - Pre-Alarm, Alarm, Alarm2, Aux Alarm (n/o) and Fault (n/c)
Ratio y tipo de salida	500 mA @ 30 V

#### Físico

Dimensiones físicas	427 x 372 x 95 mm (W x H x D)
Peso neto	5.2 kg
Color	Crema
Tipo de Montaje	Montaje en pared
Entradas de cable	6 x M20
Material (caja)	Chapa de acero

#### Medioambiental

Temperatura de funcionamiento	-10 to +60°C (EN54-20)
Humedad relativa	0 to 90% noncondensing
Entorno	Interior
Clasificación IP	IP40



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 7 March 2024 - 11:23