

ACL800SUW-RDPX-G

ACL800 EM/CASI/HID Prox reader - Wiegand, HID Pass-Through, Surface mount, Grey

Product description

These surface mount proximity readers includes a buzzer and a tri-color LED for state indication (access granted, access denied or idle). ACL800SUW-RDPX is capable of reading Casi Rusco, EM and HID compatible cards/fobs (125 kHz).

The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.

Card technology

The readers are compatible with the TruPortal (125 KHz) credential range. The Proximity card type can be selected through DIP switches in "HID only", "HID and EM", "HID and Casi", "Casi only" or "EM only" and Wiegand outputs automatically according to the card type.

Compatibility

The ACL800 reader range is compatible with the TruPortal learn-in reader (TP-RDR-LRN) for learning-in credentials in access control panels like TruPortal. This compatibility is provided for both the 125 KHz and the 13.56 MHz credentials, while using the full wiegand format length in the management software (also with other third-party packages). There are different mounting possibilities: either flush mounted within the electrical wall sockets or surface mounted with a stylish, small, modern-looking molded design.



Details

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Compatible with the TruPortal learn-in reader (TP-RDR-LRN)
- Backlight illumination
- 125 KHz EM/CASI/HID Proximity reader

ACL800SUW-RDPX-G

ACL800 EM/CASI/HID Prox reader - Wiegand, HID Pass-Through, Surface mount, Grey

Especificaciones técnicas

Sistema

Distancia máxima del lector al panel	50 m
CSN (Numero Serie de la Si Tarjeta)	
No. de LED's	3
Idioma del manual de instalación	English

Tecnología

Tipo de lector	Proximidad
Lector funcionando - transmitiendo frecuencia	125 KHz
Tecnología 125 KHz soportada	EM4102, GE ProxLite/CASI Prox, HID Prox

Interfaz y conexiones

Interfaz	Wiegand
Tipo de conector	Coleta
Longitud del cable extensible	100 cm

Tipo de tamper

Tamper antipalanca	No
Apertura de tamper	Si

Operación

Autónomo	No
Teclado PIN	No

Eléctrico

Tipo de fuente de alimentación	VCC
Valor de la fuente de alimentación	9 to 14 VDC
Consumo de corriente	100 mA at 12 VDC

Físico

Dimensiones físicas	92 x 52 x 27 mm
Peso neto	300 g
Peso de envío	310 g
Color	Gris
Material	Aluminio moldeado
Factor de forma	Mullion
Tipo de montaje	Montaje en Superficie

Medioambiental

Entorno	Interior, Exterior
Temperatura de almacenamiento	-20 to +50°C
Humedad relativa	5 to 93% noncondensing

Regulador

Cumplimiento	CE, RoHS
--------------	----------

Operation

Green LED	Potential Free
Red LED	Potential Free
Orange LED	Idle mode
Illumination	Blue backlight (programmable on/off control)
Buzzer	1 (internal)



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 29 March 2024 - 9:43