

# DB950R

## Base con relé para detectores de la serie 900/950.

### General

---

The DB950R incorporates a low power relay to control field equipment such as automatic door closers. It provides a set of voltage-free relay contacts controlled by the remote output of a 950 or 990 series detector.

### Unique addressing

---

A unique, patented addressing method provides simple, user-friendly and accurate identification of detector location whereby a coded card, inserted in the base, is read by any detector as it is plugged in. All the sensing electronics are in the detector, but the location information is held in the base. Addressing errors during maintenance and service are eliminated. Pre-coded and pre-numbered address cards are also available. These address cards simplify and speed up installation and commissioning.

### Installation

---

Robust, multi-wire screw terminals allows cables to be connected with ease, providing a secure connection platform. The relay output offering a standard change-over contact is integrated into the detector base.

### Operation

---

The relay output is activated by the remote indicator output of the detector installed on the base. Under normal conditions, this output activates whenever the installed detector is in alarm. If the control panel allows the functionality, the remote indicator output may be individually controlled and programmed, allowing for a low cost, potential free relay output to be available for basic control applications.



### Detalles

---

- Provides one potential free change over contact
- Series 950 and 990 compatible
- Supports standard 900 series address card
- Includes locking mechanism for detectors
- Screw terminals for multiple wires

# DB950R

Base con relé para detectores de la serie 900/950.

## Especificaciones técnicas

### Eléctrico

Consumo de corriente	<1 µA (quiescent) <40 µA (active)
Terminales	Contact rating 1A @ 30 VDC

### Físico

Dimensiones físicas	100 x 24 mm (Ø x H)
Peso neto	100 g
Color	Blanco

### Medioambiental

Temperatura de funcionamiento	-20 to +70°C
Humedad relativa	10 to 95% noncondensing
Entorno	Interior

### Regulador

Certificación	EN54-5, EN54-7
---------------	----------------

