

## DC143

**Contacto magnético para superficie, polarizado, terminal de tornillos. Apertura operativa máx. 9-75mm.**

### **Industrial Surface Mount Contact**

---

The DC116 series features a wider make distance and works better on steel without time-consuming installation of brackets. A wider break distance helps prevent false alarms caused by loose fitting doors.

### **Applications**

---

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.



### **Detalles**

---

- Rugged design for industrial applications
- Models for use on steel without time-consuming brackets
- Concealed terminals resist tampering and inadvertent shorting
- Easy clamping terminals speed installation
- Mounting screws included

# DC143

Contacto magnético para superficie, polarizado, terminal de tornillos. Apertura operativa máx. 9-75mm.

## Especificaciones técnicas

---

### General

Tipo de Aplicación	Montaje en Superficie
Tipo de contacto	CO
Conectividad	Screw

### Con cable / inalámbrico

Con cable / inalámbrico	Cableado
Brecha de funcionamiento	9 mm (min.); 31 mm (max.)

### Físico

Dimensiones físicas	99 x 17 x 15 mm
Color	Beige



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de [es.firesecurityproducts.com](http://es.firesecurityproducts.com) o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 9:33