

# IU955 Aislador de lazo inteligente. Serie 950.

#### General

The IU955 intelligent isolator is designed to protect a 900 series fire detector loop in the event of a short circuit fault. The isolator divides a loop into groups of 20 devices as a rule, so that in the event of a short circuit, no more that 20 devices will be affected and become inoperable.

#### Design

The IU955 has particularly low non-isolating resistance to allow for more isolators to be installed per loop without affecting the overall cable length of that loop.

#### **Requirement for Isolation**

Addressable fire detection systems are normally designed as loops, with the connecting wires starting and finishing at the control panel. Detectors and interfaces are connected at intervals along these cables.

When short circuits occur on a loop, the consequences can be serious, in worst case making the affected loop entirely inoperative. The purpose of isolating circuits is to protect the loop in the event of a short circuit by disconnecting the part of the loop where the short circuit has occurred, thereby isolating the short circuit and only rendering a small part of the loop inoperative. The remainder of the loop continues to function normally. When the short circuit fault has been rectified, the isolating circuitry reconnects the affected section of the loop.

The more isolators that are installed on the loop, the smaller part of the loop is affected by a short circuit condition. By regulation there should never be more than 32 devices between isolators, but it is recommended that isolation is placed at least at every entry and exit point to a zone.



#### **Detalles**

- No addressing required
- Automatic reset
- Visual "Isolated" indication

## IU955 Aislador de lazo inteligente. Serie 950.

### Especificaciones técnicas

Eléctrico	
Voltaje de	17 to 28 VDC
funcionamiento	
Físico	
Dimensiones físicas	32 x 100 mm (H x D)
Medioambiental	
Temperatura de	-20 to +60°C
funcionamiento	
Temperatura de	-30 to +80°C
almacenamiento	
Humedad relativa	0 to 95% noncondensing
Entorno	Interior
Regulador	
Certificación	EN54-17
Electrical	
Supply voltage	17 to 28 VDC
Protocol pulses	5 to 9 V
Power up time (max)	10 ms
Continuous loop current (max)	1 A
Short circuit switching (max)	3 A
Quiescent current (max)	45 μΑ
On resistance (max)	0.2 ohm
Isolation	
Isolation voltage	13.6 - 14.8 V
Re-connect voltage	12.9 -17.5 VDC
Test current	35 - 50 mA
Isolation current (max)	6.4 mA
Environmental	
Operating temperature	-20°C to +60°C
Storage temperature	-30°C to +80°C
Humidity (no condensation)	0 - 95 % RH
Size (h x d)	
	32 x 100 mm



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.