

RXI4N8

Receptor Universal de 433 MHz

General

The "Quickbridge" Loop Receiver is a universal wireless receiver compatible with any standard hardwired control panel. Available with a wide range of wireless devices, including keyfobs, passive-infrared detectors, door/window detectors and medical panic buttons, every system can be made virtually wire-free.

The Quickbridge supports the Learn-Mode technology, which means that each device has its own factory-programmed id, so the receiver automatically recognizes each device. This dramatically reduces installation time and eliminates programming errors in the field.

Compatability

The QuickBridge is compatible with all current Learn Mode sensors (433.92 MHz), panic button transmitters, two- and four-button keychain touchpads, with the exception of smoke detectors.



Detalles

- 433.92 MHz Learn-Mode Technology
- Support for up to 16 wireless sensors and 45 keyfobs and panic buttons
- Monitors alarm, battery, tamper and supervisory status of transmitters
- Spatial diversity receiver with enhanced reception
- Jamming Detection
- 8 programmable zone outputs
- Zone openings and closings indication
- Non-volatile memory to prevent programming information and sensors IDs loss in case of power failure
- Compatible with all popular/current control panels

RXI4N8

Receptor Universal de 433 MHz

Especificaciones técnicas

General

Tipo de expansor	Expansor inalámbrico
------------------	----------------------

Salidas

En placa	z1 to z8 ; Battery ; Supervision
----------	----------------------------------

Tipos de salidas	Open collector
------------------	----------------

Inalámbrico

Frecuencia de funcionamiento	Legado de 433 MHz
------------------------------	-------------------

Eléctrico

Voltaje de funcionamiento	10 to 14Vdc
---------------------------	-------------

Consumo de corriente	60mA maximum
----------------------	--------------

Físico

Dimensiones físicas	103 x 131 x 25 mm (excluding antenna)
---------------------	---------------------------------------

Medioambiental

Temperatura de funcionamiento	0 to +40°C
-------------------------------	------------

Regulador

Cumplimiento	CE
--------------	----

Outputs

Maximum applied voltage	16 VDC
-------------------------	--------

Maximum sink current	50 mA (typical), 15 mA (minimum)
----------------------	----------------------------------



Como empresa innovadora, Carrier Fire & Security se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 5 May 2023 - 10:29