



SMA-L-PROX

MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE

MA SIGMA Lite & MA SIGMA Lite Plus Series

Engineered with the same attention to detail and performance as their predecessor, the MorphoAccess® SIGMA Lite terminals are specifically designed to equip narrow mounting surfaces, such as glass/aluminum door Mullions, turnstiles or server rack doors. With two designs (with touchscreen: MA SIGMA Lite Plus ; without touchscreen: MA SIGMA Lite) and multiple embedded card reader options, there are a variety of models to address the widest range of deployment scenarios, both indoor and outdoor.

Embedded web server

The MA SIGMA Lite Series enables on-device enrollment, terminal configuration and transaction log retrieval thanks to the embedded web server. Moreover, it can be used with any device (PC, laptop, tablet, smartphone), any operating system (Windows, Android, iOS) or any web browser (Google Chrome, Mozilla Firefox, Safari and Internet Explorer).

Enhanced interactivity

Thanks to the 2.8" QVGA touchscreen on the MA SIGMA Lite Plus Series, you can benefit from an enhanced user experience. The MA SIGMA Lite Plus holds T&A in and out function keys, User ID/PIN/BioPin management and intuitive icons and live messages.

Compatible with existing installations

The MA SIGMA Lite Series can be used to upgrade an existing installation or to complement the installation with MorphoAccess® SIGMA (Lite) devices using the MorphoManager application or MIK SDK on a Morpho network or the SecureAdmin™ application or SecureSDK™ on a BioScrypt network.

Enhanced security features

The MA SIGMA Lite Series encompasses the latest and greatest anti-fraud features, such as: fake finger detection, duress finger, timed anti-pass back function and banned/authorized user lists.



Details

- Leading fingerprint technology inside - 1:10,000 user identification in 1 second
- High capacity - 30,000 templates, 250,000 IDs in authorized user list, 1 million logs
- Advanced anti-fraud features
- Flexibility - Optional Prox, iCLASS or MIFARE/DESFire contactless card reader
- Tough design - IP65 rated and vandal resistant (IK08, SIGMA Lite only)

SMA-L-PROX

MA SIGMA Lite - Prox, Multi-factor Bio/Card, HID Prox, 500 users, IP65, CE

Especificaciones técnicas

Sistema

Distancia máxima del lector al panel Ethernet: 100 m, RS485: 1219 m

RTE (Petición de salida) No

CSN (Numero Serie de la Si Tarjeta)

Modelo de datos personalizados No

No. de LED's 1

Tecnología

Tipo de lector Biométrico

Lector funcionando - transmitiendo frecuencia 125 KHz

Tecnología 125 KHz soportada HID Prox

Biométrico

Tipo de Biométrico Huella digital

Tipo de sensor biométrico Óptica

Interfaz y conexiones

Interfaz Ethernet, OSDP V2, OSDP V2 Secure Channel, RS-485, USB, Wiegand

Tipo de conector Red, Coleta

Longitud del cable extensible 40 cm

Tipo de tamper

Tamper antipalanca No

Apertura de tamper Si

Operación

Autónomo Si

Teclado PIN No

Eléctrico

Tipo de fuente de alimentación VCC

Valor de la fuente de alimentación 12 to 24 VDC

Físico

Peso neto 280 g

Peso de envío 325 g

Color Negro

Material Policarbonato

Factor de forma Sobredimensionado

Tipo de montaje Montaje en Superficie


Medioambiental

Antivandálico No

Temperatura de almacenamiento -10 to +55°C

Regulador

Cumplimiento CE, FCC, REACH, RoHS



Como empresa innovadora, Kidde Global Solutions se reserva el derecho de modificar las especificaciones de los productos sin previo aviso. Para conocer las últimas especificaciones de los productos, visite la Web de es.firesecurityproducts.com o póngase en contacto con su comercial.

Last updated on 21 May 2024 - 16:53