

SC-43-0200-0001-99

SmartCell Yhteys lähettäjä ja syöttölaite tietovyöhykkeille

Overview

The SmartCell Input Device is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device allows non fire to be monitored at the SmartCell Control Panel and to an information alert when activated. Examples may include the monitoring of doors (opening/closing), a loss of power to your fridge, flood detection and an alarm condition on your intruder system.

Features include a resistor monitored input, an alternative magnetic contact option and bidirectional 868 MHz communication.

This device is third party certified and compatible with the full SmartCell product range.



Yksityiskohdat

- Full wireless communication with panel
- Quick and easy to install
- Resistor monitored input
- Alternative magnetic contact option (magnet supplied)
- For connection to remote information devices
- NOT FOR FIRE APPLICATIONS

SC-43-0200-0001-99

SmartCell Yhteys lähettäjä ja syöttölaite tietovyöhykkeille

Tekniset tiedot

Yleinen

Langaton taajuus 868 MHz

Panos

Tulojen määrä 1

Tulon tyyppi ja luokitus Resistor monitored input

Fyysinen

Fyysiset mitat 30 x 110 x 28 mm (W x H x D)

Nettopaino 0.05 kg

Väri Valkoinen

Asennustyyppi Seinäkiinnitys

Paristot 1 x ER14505M 3.6 V lithium thionyl chloride battery (Fanso or Titus)

Ympäristö-

Käyttölämpötila -10 to +55°C

Säilytyslämpötila -10 to +30°C (with battery)
-10 to +55°C (without battery)

Suhteellinen kosteus 95% noncondensing max.

Ympäristö Sisällä

Säätely

Yhteensopivuus CE

Standardit R&TTE

