

# TX-2213-03-1

## Langaton PIR 12m 868AM Gen2



### Yksityiskohdat

---

- Proven mirror optics inside to get a dense coverage pattern
- Selectable coverage pattern using mirror masks
- Full under crawl detection
- "5D" signal processing for false alarm immunity
- Auto focus with constant range sensitivity
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 5-years battery life with 1 battery
- Holding several security approvals

# TX-2213-03-1

## Langaton PIR 12m 868AM Gen2

### Tekniset tiedot

---

#### Yleinen

Teknologia	PIR
Sovelluksen tyyppi	Seinäkiinnitys
Anti masking	Ei
Lemmikkieläinten immuuni	Ei
Kamera	Ei
Seinäkosketin KIT	On board
Ilmaisimen käynnistymisaika	1 min

#### Havaitseminen

Tunnistusalueen valinta	6 or 12m
Verhojen määrä	9
Kattavuus (näkökenttä)	86°
Ryömintäsuoja	Joo
Tavoitenopeusalue	0.3 m/s to 3 m/s

#### Langallinen / langaton

Langallinen / langaton	Langaton
Langaton taajuus	868 MHz AM

#### Sähkö-

Nykyinen kulutus	22 $\mu$ A (avg.), 50 mA (max.)
Paristot	1 x CR123 (3.0 V, 1300 mAh lithium)
Pariston käyttöikä	5 years

#### Fyysinen

Fyysiset mitat	130 x 69 x 53 mm
Nettopaino	146 g
Asennuskorkeus	1.8 to 3 m

#### Ympäristö-

Käyttölämpötila	-10° tot +55° C
Suhteellinen kosteus	95% max. noncondensing
Ympäristö	Sisällä
IP-luokitus	IP30 IK02

#### Säätely

EN50131-luokka	Luokka 2
Sertifiointi	INCERT

