177401

ZP755R-2R ROOM SNDR C/W COVER

General

The ZP755R-2R is a RED, addressable loop powered room sounder or us on ZP fire alarm systems. The ZP755R-2R combines a detector base and audible sounder in a single stylish moulding.

The ZP755R-2R is developed for applications in individual rooms, sleeping accommodation or small compartments where it is impractical or unnecessary for the sounder and detector to be combined. Installed directly onto a ZP7 wiring loop - the ZP755R-2R enables the system designer to offer a complete addressable system on a single pair of wires. Installation costs are greatly reduced, whilst system integrity, sounder options and programmed alarm organisation are significantly increased. Time on site is further reduced as the moulding plugs directly into a first fix base – eliminating the need for any wiring directly to the device.

Advanced acoustic design

High efficiency acoustic design and a low energy, sound gun transducer, enable combinations of up to 60 sensors and 60 sounders to be connected to a 1 km loop of 1.5 mm² cable. In systems where loop lengths or current requirements are excessive, the ZP755R-2R sounders can be locally powered from an external power supply.

Output Test and Tone Selection

The ZP755 range of notification devices features a unique self-test facility which is automatically activated during routine sounder testing. A built in microphone circuit measures sound output level and automatically signals the sounder address and location to the control panel, should the output test fail.

Continuous, intermittent and two-tone outputs are available from which any combination can be chosen to provide alert and evacuate for two stage alarms. Sound types comply with most international codes (e.g. BS 5839 Part 1 recommended frequencies). The ZP755R-2R features a sound output of up to 90dBA and a volume control for areas where a reduced sound output is required.



Détails

- Powered directly from the ZP loop
- Up to 60 detectors and 60 sounders directly on the loop wiring
- Plug in base – no direct wiring connections
- High efficiency sound gun transducer
- Wide range of international sound types and frequencies
- EN54:3 Approved and CPR certified

177401
ZP755R-2R ROOM SNDR C/W COVER

Spécifications techniques

Général

Compatibilité	All ZP7 addressable systems
Méthode d'adressage	DIP Switches
Contrôle	Device removal, Device type, Open circuit, Short circuit, Sound output

Électrique

Tension de fonctionnement	Loop powered: 19.5 to 20.5 V Externally powered:18 to 30 VDC

Sirène

Niveau de sortie	<70 dB(A) (tone dependant)
Tonalités sélectionnables	Sound types: User configurable

Caractéristiques physiques

Dimensions physiques	127 x 69 mm (Ø x H)
Poids net	205 g
Couleur	Rouge
Type de montage	Montage en surface
Matériel	Thermoplastique moulé

Environnement

Température de fonctionnement	-10 to +60°C
Température de stockage	-20 to +70°C
Humidité relative	10 to 95% noncondencing
Environnement	Intérieur
Indice de protection	IP21C

Régulateur

Certification	CPR, EN54-3

Physical

Mounting	Surface mount with plug in base - SPB-2R (White)

Loop current

Quiescent (when loop powered)	820 µA
Active (when loop powered)	4.5 mA
Quiescent (when externally powered)	470 µA
Active (when externally powered)	500 µA

Devices per loop (max.)

	60 (1 km loop of 1.5 mm² cable, 50 m to first device)

Wiring

	2 core loop

General

Addressing method	7 way dipswitch

Produits compatibles

Catégorie	Référence	Description
Module de notification	70802	Red Cap for ZP755B Series Notification Devices
Module de notification	SPB-2R	Plug-in Base, RED



KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 23 February 2026 - 15:56