2010-2-PIB-8O

Addressable Fire Panel Accessory - Peripherals Interface Board 8 Outputs

Overview


The 2010-2-PIB-8O Peripherals Interface Board is an accessory of the small to medium size intelligent addressable life safety control systems. In total there are 4 variants of this board. The 2010-2-PIB-8O is a reduced variant of the 2010-2-PIB and is perfect if your only looking for having additional supervised outputs to interface other electronic equipment on site.

Functionality

The 2010-2-PIB-8O Peripherals Interface Board provides eight outputs for compatible control panels. The board can be powered from the control panel or from an external power supply, providing 24 VDC to each of the supervised outputs. Outputs are supervised for short circuit and open circuit faults.

Mounting & connections

The board can be plugged directly on the front of the main board inside the big size control panel variants on top of the new release 3 chassis. No additional wiring is required. You can use the pluggable connectors to make your connections to the field wiring. Connect an external power supply to the board directly to reduce the load of your system.



Détails

- 8 supervised outputs
- Option to externally power
- Pluggable connectors

2010-2-PIB-8O

Addressable Fire Panel Accessory - Peripherals Interface Board 8 Outputs

Spécifications techniques

Général

Compatibilité	Release 3 hardware / firmware

Électrique

Type de bloc d’alimentation	VDC
Tension de fonctionnement	24 VDC
Consommation de courant	40 mA max. (standby) 4050 mA max. (activated)

Sortie

Type de sortie et classe	500 mA at 25°C (activated, per output)

Caractéristiques physiques

Types de format	Large
Dimensions physiques	105 x 192 mm (W x H)
Poids net	126 g
Poids à l'expédition	220 g
Type de montage	En armoire

Environnement

Température de fonctionnement	+5 to +40°C
Température de stockage	-20 to +50°C
Humidité relative	10 to 95% noncondensing

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE
Certification	CPR
Normes	EN54-2, EN54-13

End-of-line termination

Output (typical)	EOL 15 kOhm, 1/4 W resistor
Output (EN 54-13)	EOL Class B (EN 54-13) device

KIDDE COMMERCIAL

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 31 August 2026 - 8:53