9-30441

Excellence Addressable Panel Interface Card (APIC)

Description

The 9-30441 is an interface which can be fitted directly into the ModuLaser display module. The card plugs into the main control board inside the display module enclosure. The board enables each detector (in the cluster or on the SenseNET network) to be directly addressed and communicate with the main fire control panel via the Excellence protocol.

Plug in terminals

Wiring onto the addressable loop is by way of plug in terminals located on the ModuLaser Minimum display or ModuLaser Standard display backplane. The APIC address range is easily adjusted by switch settings prominently positioned on the APIC card. The start and stop address of the range must be selected during installation, and mimics the SenseNet address range.

Single Display and Command Display modes

The Excellence APIC has two distinct modes of operation; single display and command display. When the interface is mounted in a ModuLaser Minimum or Standard Display module, each module in the cluster appear as a single address on the Excellence loop and the detector status is read from that address. Command Display mode is used when monitoring the status of multiple detectors and/or ModuLaser clusters with consecutive addresses from a single Excellence APIC card.

Détails

- Simple addressing onto the addressable loop
- Ribbon cable connection – no hard wiring
- Piggy backs onto ModuLaser display module
- Ease of address setting
- Avoids the need to manually wire inputs and outputs

9-30441
Excellence Addressable Panel Interface Card (APIC)

Spécifications techniques

Général

Compatibilité	Aritech protocol

Caractéristiques physiques

Dimensions physiques	101 x 68 mm (W x H) (PCB)

Environnement

Température de fonctionnement	-20 to +60ºC
Humidité relative	10 to 95% noncondensing
Environnement	Intérieur

Régulateur

Conformité	CE, REACH, RoHS 3, WEEE
Certification	BOSEC, CPR
Normes	EN54-17, EN54-18

Physical

Mounting	Ribbon cable with plug and socket - fixes to allotted space inside ModuLaser display module

Produits compatibles

Catégorie	Référence	Description
Module de détection	9-30441-JUM	
Module de détection	9-30780	AirSense Stratos ModuLaser, Minimum Display Module
Module de détection	9-30780-KID	Kidde Senator ModuLaser, Minimum display module
Module de détection	9-30781	AirSense Stratos ModuLaser, Standard display module
Module de détection	9-30781-KID	Kidde Senator ModuLaser, Standard display module
Module de détection	9-30782	AirSense Stratos ModuLaser, Command display module
Module de détection	FHSD8300	LaserSense ModuLaser, Minimum display module
Module de détection	FHSD8310	LaserSense ModuLaser, Standard display module
Module de détection	FHSD8320	LaserSense ModuLaser, Command display module

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 31 August 2026 - 8:43