
ACL580FI

Keypad, stainless steel, flush mount, standalone

Advanced keypads for access control and home automation

These standalone robust keypads are designed to operate in both indoor and outdoor environments. ACL580 keypads are available with backlit metallic/plastic keys and in a variety of plastic or metal housing options. These keypads offer elegant looks with a host of programmable options such as backlit keys, 1000 users, invalid code lockout, 2 pushbutton inputs, support for ACL870 push buttons, adjustable unlock timer etc. Can control two doors. Available in metal or plastic and surface or flush mounted.



Détails

- Indoor/outdoor
- Stainless steel front and metal keys
- Dust proof and water-resistant (IP65)
- Up to 1000 user codes
- Request To Exit using normal RTE button or ACL870 type pushbutton
- Codes can be 1 to 8 digit long
- Users can be assigned any of the available relays
- 30 second lockout after eight consecutive invalid PINs
- Red and green LED (relay status) and orange LED (Programming)

ACL580FI

Keypad, stainless steel, flush mount, standalone

Spécifications techniques

Général

Interface utilisateur	Touch Buttons
Gamme de produits	Autonome
LED d'état	3

Communication

Type de communication	Câblés

Entrées / sorties

Entrées	2
Type d'entrée	Request-To-Exit
Sorties	2
Type de sortie	2 SPDT relays, Latch or pulsed mode (01 to 99 seconds)

Électrique

Tension de fonctionnement	12 / 24 VAC/VDC
Consommation de courant	150 mA max

Caractéristiques physiques

Dimensions physiques	105 x 140 x 1.5 mm (top cover) 84 x 108 x 32 mm (bottom)
Types de format	Vertical
Type de montage	Montage encastré
Matériel	Acier inoxydable

Environnement

Température de fonctionnement	-20 to +50°C
Humidité relative	95% noncondensing
Indice de protection	IP65

Régulateur

Conformité	CE
Certification	CE

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 18 June 2026 - 14:24