ACL875SU-B

ACL800 Keypad - Stand alone, Surface mount, Black

Product description

"ACL875SU range is a standalone digital keypad for access control applications with backlight keys, 99 user codes, 2 outputs (relay and transistor) and 1 push button input. These keypads are available in three different color finishes. Authorized users can be assigned specific codes for use in access control applications, electrical switching and arming/disarming alarm systems. The Users can be assigned to activate the first, the second or both outputs. There is a 30 seconds lockout after 8 successive invalid PIN Codes. The tamper switch output can trigger the alarm system, if an attempt is made to open or remove the unit from the wall."

The ACL800 range

The ACL800 Series consists of all the required elements to establish a range with a state-of-the-art design. This new range, consisting of readers, stand-alone keypad readers and Request-To-Exit touch sensitive push buttons, provides all you need for a coherent look-and-feel attractive project. Moving forward, this product range will be further developed with biometric readers.



Détails

- Indoor/outdoor
- Dust proof and water-resistant (IP65)
- Up to 99 user codes
- Codes can be 1 to 8 digit long
- Attractive and timeless design
- Includes a buzzer
- Tri-color LED's
- Surface mount
- Backlight illumination
- Keypad

ACL875SU-B

ACL800 Keypad - Stand alone, Surface mount, Black

Spécifications techniques

Système

Nbre de LED	1
Nbre de couvercles inclus	1
Langue du manuel d'installation	English

Interface et connexions

Type de connecteur	Queue cochon
Longueur de la queue de cochon	100 cm

Type d'autoprotection

Levier d’arrêt inviolable	Non
Ouverture d'autoprotection	Oui

Opération

Autonome	Oui
Nbre d'utilisateur en mode autonome	99
Code PIN clavier	Oui
Longueur du code PIN	6

Électrique

Type de bloc d’alimentation	VDC
Valeur de l'alimentation	5 to 24 VDC
Consommation de courant	100 mA at 24 VDC 30 mA at 24 VDC

Caractéristiques physiques

Dimensions physiques	92 x 51 x 27 mm
Poids net	140 g
Poids à l'expédition	190 g
Couleur	Noir
Matériel	ABS
Types de format	Mullion
Type de montage	Montage en surface

Environnement

Environnement	Intérieur, Extérieur
Température de stockage	-20 to +50°C

Régulateur

Conformité	CE, RoHS

Operation

Keys	Backlit Metallic
Master Code For Programming	1
User Codes	99
Green LED	Output 1 status
Red LED	Output 2 status
Orange LED	Programming status and Key Press
Keypad blocking	Blocked for 30 seconds with beep noise after 8 consecutive incorrect codes
Buzzer	1 (internal)

Technology

Outputs	1 Relay (2A) & 1 Transistor (250mA)
Relay time	Latching or timed from 1 to 99 seconds
Memory	EEPROM (programming is safe in case of a power outage)

Tamper type

Tamper Protection	When open or dismantled

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 September 2023 - 9:56