AD105-0100

Alarmline II Digital LHD Cable 105°C (221°F) w/ PVC Sheath - 100m

General

The AD105-0100 is a Digital Linear Heat Detection (LHD) cable with a 105°C (221°F) fixed temperature activation rating. It has a Standard PVC outer sheath making it suitable for internal applications and is supplied in 100m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' ,'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Détails

- cUL/UL 521 approved
- FM approved (Class 3210)
- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD105-0100

Alarmline II Digital LHD Cable 105°C (221°F) w/ PVC Sheath - 100m

Spécifications techniques

Électrique

Tension de fonctionnement	0 to 30 VAC, 0 to 42 VDC
Nbre de fils conducteur	2

Détection

Alarme température	+105ºC

Conducteur

Résistance	91 Ω/km (27.7 Ω / 1000 ft.)
Capacitance	<73 pF/m (<22 pF/ft.)
Induction	<1.65 µH/m (<0.5 µH/ft.)
Couleurs de base	White

Caractéristiques physiques

Poids net	2 kg
Couleur	Blanc
Type de montage	Support de câble

Environnement

Humidité relative	0 to 100% noncondensing
Environnement	Intérieur, Extérieur
Protection	PVC Sheath

Régulateur

Certification	CE, FM, UL

Mechanical

Outside diameter (Nominal)	3.6mm ± 0.12mm

Environmental

Ambient temperature (max)	69°C (156°F)

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 4 August 2026 - 8:33