AD68P-0500

Alarmline II Digital LHD Cable 68°C (155°F) w/ Polypropylene Sheath - 500m

General

The AD68P-0500 is a Digital Linear Heat Detection (LHD) cable with a 68°C (155°F) fixed temperature activation rating. It has a Polypropylene outer sheath for increased chemical protection in caustic environments and is supplied in 500m lengths.

The AD range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The AD range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable provides a simple switch operation which when used with a combination of end-of-line (EOL) monitoring and alarm trigger resistors can signal an alarm to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit.

Location Control Unit

Additional to the LHD sensor cable, an optional digital location control unit which monitors the sensor cable and can identify along the length of the sensor cable where an alarm condition has occurred, is also available.

Cable fixings for all applications

A range of 'edge' ,'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Détails

- Up to 3000m (10,000ft per zone)
- Detection along total cable length
- Optional extrusions for different environments
- Simple maintenance free installation
- Suitable for use in hazardous areas
- RoHS Compliant

AD68P-0500

Alarmline II Digital LHD Cable 68°C (155°F) w/ Polypropylene Sheath - 500m

Spécifications techniques

Électrique

Tension de fonctionnement	0 to 30 VAC 0 to 42 VDC
Nbre de fils conducteur	2

Conducteur

Résistance	~100 ohms/km per leg (30.4 ohms/Kft)
Capacitance	88 to 150 pF/m
Induction	540 to 1050 nH/m

Caractéristiques physiques

Dimensions physiques	4.5 mm ±0.12 mm (nominal outside diameter)
Poids net	13.6 kg
Couleur	Rouge
Type de montage	Support de câble

Environnement

Température de fonctionnement	45°C (113°F)
Humidité relative	0 to 100% noncondensing
Environnement	Intérieur, Extérieur

Régulateur

Certification	CE

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 4 August 2026 - 8:30