ADE88-0100

AlarmLine II Digital EN LHD cable 88°C, 100 m

General

The ADE88-0100 is a Digital Linear Heat Detection (LHD) cable with a 88°C fixed temperature activation rating. The ADE range of digital sensor cables provides a very simple fixed temperature heat detection system which can be used in many applications where other forms of detection are not suitable.

Operation

The ADE range of digital LHD cables contains a pair of twisted, low resistance, tri-metallic conductors sheathed with advanced temperature sensitive polymers. The cable operates by softening the insulation of the conductors, the tension of the twisted conductors then causes the two cores to fuse together. The sensor cable is used in combination with the controller and end-of-line (EOL) unit, and can connected to any fire monitoring equipment through any monitored input i.e. conventional detection zone or addressable interface unit to signal an alarm condition.

Alarm location

The control unit can identify along the length of the sensor cable where an alarm condition has occurred. The alarm location is then indicated on the display of the controller. Both zone are displayed at the same time.

Cable fixings for all applications

A range of 'edge' ,'A' , 'P' , and 'T' clips allow the cable to be properly installed. The clips provide heat insulation as well as holding the cable at the correct distance from cable trays, steel works, ceilings and walls.



Détails

- EN54-28:2016 approved
- Low-Smoke Zero Halogen
- Up to 1000 m
- Detection along total cable length
- Flame retardant
- Simple low maintenance installation
- RoHS compliant

ADE88-0100

AlarmLine II Digital EN LHD cable 88°C, 100 m

Spécifications techniques

Électrique

Tension de fonctionnement	0 to 49 VAC, 0 to 74 VDC
Spécification du câble	Insulation 1kV
Nbre de fils conducteur	2

Détection

Alarme température	+88ºC

Conducteur

Résistance	2.5 ohm per m
Capacitance	<100 pF per m
Induction	<3.2 uH per m

Caractéristiques physiques

Dimensions physiques	Diameter 5.72 mm +/- 0.12 mm (0.225” +/- 0.0005”)
Couleur	Blanc
Type de montage	Support de câble

Environnement

Humidité relative	0 to 98% noncondensing

Régulateur

Certification	CE, EN54-28

Environmental

Ambient temperature	-40 to +65°C

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 4 August 2026 - 8:33